

# Wireless Display Module

Art.-Nr. FU8403

Seite 1 von 2



The wireless display module provides a quick overview of the status of the Secvest detectors in the house. You can see at a glance whether a detector or a window is open or closed. The module has a convenient status display for the FTS 96 E wireless window protection system and the Secvest wireless magnetic contact detectors - even in stand-alone mode without the alarm panel. However, if the window protection systems are operated in combination with a Secvest 2WAY, the display module is an important supplement: window protection system and wireless magnetic contact detectors can be taught-in to the display module and the alarm panel at the same time.

## Technologies

- 16 individually programmable display channels
- Compatible with mechatronic and Secvest wireless opening detectors
- 2 LED status indicators
- Standalone solution for displaying the status of connected detectors

## Technical data - Wireless Display Module

Compatible with	Secvest, Terxon
DC voltage supply	12 V
Dimensions	(WxHxD) 135x220x45 mm
Display	18 LED status displays
Environmental class	I
Height	220 mm
Housing material	ABS
Length	45 mm
Max. operating temperature	50 °C
Max. receiving range (building)	30 m

# Wireless Display Module

Art.-Nr. FU8403

Seite 2 von 2

---

## Technical data - Wireless Display Module

Max. receiving range (free field)	100 m
Min. operating temperature	0 °C
Modulation	FM
Net weight	0,52 kg
Power consumption	150 mA
Radio frequency	868 MHz
Width	135 mm