

## 2 Network Outdoor Cameras + Accessory

Art.-Nr. TVVR36520S

Seite 1 von 2

### Technical data - 2 Network Outdoor Cameras + Accessory

Alarming	E-Mail
Amplifier control	AGC
Backlight compensation	Soft-WDR
Camera type	Day/night
Certifications	CE, RoHS, REACH
Connections	1 x RJ45, 1 x DC
DC voltage supply	12 V
Electronic shutter	1/3 - 1/100000 s
Focal length	4 mm
Frame rate	25 fps @ 1280x960, 25 fps @ 1280x720
Height	82 mm
Horizontal viewing angle	69,4 °
IP protection class	66
IR LEDs	30
IR range (up to)	10 m
Image sensor	1/3" Progressive Scan CMOS
LAN network access	RJ-45 Ethernet 10/100 Base-T
Language of instructions	DE, UK, FR, NL, DK, PL, RU, SWE, IT, ES
Language packing	DE, UK, FR, NL, DK, ES, IT, PL, SWE
Max. operating temperature	50 °C
Max. resolution @ frame rate	1280 x 960 @ 25 fps
Min. operating temperature	-10 °C
Minimum illumination (IR)	0 lx
Minimum illumination (colour)	2 lx
Motion detection	3 zones
Net weight	500 kg
Network camera protocols	IPv4, IPv6, TCP/IP, HTTP, UPnP, RTP/RTSP, SMTP, DHCP, NTP, DNS, DDNS
Noise reduction	DNR
ONVIF	Profile S
OSD language	DE, UK, FR, NL, DK, PL, RU, SWE, IT, ES
Pixels (effective)	1280 x 960 pixel
Pixels (total)	1280 x 960 pixel
Power consumption	580 mA
Pre/post alarm memory	Yes
Resolution modes	Main Stream: 1280 x 960, 1280 x 720, 704 x 576, 640 x 480
Software	ABUS VMS, IPCam App
Technology	IP

## 2 Network Outdoor Cameras + Accessory

Art.-Nr. TVVR36520S

Seite 2 von 2

---

### Technical data - 2 Network Outdoor Cameras + Accessory

Video compression	H.264, MJPEG
Video system	IP