

# Smartvest Wireless Remote Control

Art.-Nr. FUBE35001A

Seite 1 von 2



Arm and disarm with the push of a button

In addition to the smartphone and tablet option, the Smartvest Wireless Remote Control offers you another streamlined and convenient option for operation - at the push of a button, without the need for a PIN code. With this option, you can both arm and disarm the Smartvest or, in an emergency, trigger a panic alarm at the touch of a button. Using the app, the button can also be configured so that certain cameras or the siren are activated when the buttons are pressed. The Smartvest Wireless Remote Control thus provides basic control options in a compact and handy form ensuring it is simple and intuitive to use.

Remark:

The Smartvest Wireless Remote Control is protected against so-called replay attacks by an integrated security mechanism. All switching commands to the Smartvest alarm panel are individualized and thus not reproducible by unauthorized third parties.

## Technologies

- Smartvest extension for operation without a mobile device
- Immediate operation at the push of a button and with no need for a PIN code
- Buttons for arming and disarming the Smartvest
- Panic alarm that can be triggered at the push of a button
- Individual configuration of buttons to automatically activate additional components (cameras, sirens, etc.) simultaneously
- Visual feedback via blue LED
- Low battery notification sent to the Smartvest alarm control panel
- Small, portable and easy to use
- Security-mechanism for protection against Replay-attacks

# Smartvest Wireless Remote Control

Art.-Nr. FUBE35001A

Seite 2 von 2

## Technical data - Smartvest Wireless Remote Control

Battery - battery operation	Yes
Battery - max. battery life	2 y
Battery - quantity	1
Battery - type	CR2032 (3V)
Colour	White
Compatible with Secvest	No
Compatible with Smartvest	Yes
Dimensions	(B x L x H) 30 x 14 x 60 mm
Display	LED
Gross weight	0,056 kg
Housing material	Plastic
Max. humidity	80 %
Max. operating temperature	40 °C
Min. humidity	10
Min. operating temperature	0 °C
Net weight	0,022 kg
Power consumption	15 mA
Radio frequency	868 MHz
Radio modulation	FSK
Standby power consumption	0,005 mA
Transmission power	4,5 dBm
Wireless range	(Depending on installation) 30 - 100 m