

ABUS EasyLook Monitor

Art.-Nr. PPDF17000M

Seite 1 von 2

Technical data - ABUS EasyLook Monitor

Alarming	Acoustic warning signal
Battery - battery operation	Yes
Battery - quantity	2
Battery - runtime	Up to 2 hours
Battery - type	5200mAH rechargeable Battery
Channel width	20/40 MHz
Colour	Black
Compatible with Secvest	No
Compatible with Smartvest	No
Compatible with wAppLoxx	No
Connections	Power: DC plug / USB 2.0
DC voltage supply	12 V
Dimensions	(W x L x H) 199 x 32 x 123 mm
Encryption	WPA2
Frequency range	2,403 - 2,478 GHz
Housing material	Plastic
Loudspeaker	Yes
Max. operating temperature	40 °C
Microphone	Yes
Min. operating temperature	0 °C
Modulation	DSSS , OFDM
Monitor type	7" Capacitive Touchscreen
Net weight	0,3 kg
Number of channels	4
OSD language	DE, GB, FR, NL, DK, IT
Plug type	DC-plug: 5,5 x 2,1 mm
Power consumption	8,4 W
Recording modes	Schedule, motion detection
Recording resolution @ frame rate per camera	3MP @15 fps
Resolution	1024 x 600p
Resolution modes	3 MP (2304 x 1296)
Screen diagonal	7 in
Sensitivity	-88 dBm
Storage medium	MicroSD Class 10 (max. 128GB)
Technology	Radio
Transmission channels	13
Transmission power	20 dBm

ABUS EasyLook Monitor



Art.-Nr. PPDF17000M

Seite 2 von 2

Technical data - ABUS EasyLook Monitor

Video compression	H.264+
Views	1 / 4 (Quad)
Wireless range	(Depending on installation) 20 - 50 m