

IP Tube 8 MPx (4K, 2.8 mm)



Security Tech Germany

Art.-Nr. IPCB68515A

Seite 1 von 4



4K 24/7 outdoor surveillance

The IP Tube provides video streams in 8 MPx resolution with up to 20 fps. The dust- and water-resistant IP67 housing is well suited for outdoor use. Due to integrated IR LEDs with a range of up to 50m, the camera can be used day and night. Access to the camera is possible at any time via app.

Universally applicable

The IP Tube IPCB68515A is designed for universal usage overlooking long distances due to the combination of IP67 weatherproof housing, 50m IR range and a 2.8 mm lens with a horizontal viewing angle of 102°.

Recording and compatibility

The recording can be done either on an ABUS recorder, 3rd party video management software or locally on a microSD card. Furthermore, the camera is compatible with the ABUS Secvest alarm center and the ABUS access control system wAppLoxx.

Comfortable installation

The IP Tube is mounted on the ceiling or optionally on the wall. We recommend the ABUS installation box (TVAC31350), which allows a protected cabling to wall or ceilings. The free "ABUS IP Installer" software is available for simple setup in the network. The software finds the camera quickly and easily within the network and supports during the installation process.

Note: The camera does not come with a power supply, as it can be powered via PoE.

Technologies

IP Tube 8 MPx (4K, 2.8 mm)

Art.-Nr. IPCB68515A

Seite 2 von 4

- 8 MPx (4K) Resolution: 3.840 x 2.160 @ 20 fps
- 2.8 mm fixed lens
- 120 dB WDR function to compensate for image contrasts
- Vandalism and weather protected housing (IK10 & IP67)
- IR LEDs (range up to 50m)
- Supports H.264, H.265, MJPEG (incl. dynamic GOP)
- microSD card slot for internal data storage
- 12 V DC & PoE (802.3at)

Technical data - IP Tube 8 MPx (4K, 2.8 mm)

| | |
|---|--|
| Alarming | E-Mail, NAS, FTP |
| Aperture at minimum illumination (colour) | F2.0 |
| Backlight compensation | WDR, BLC, HLC |
| Camera type | Tube |
| Colour | RAL9003 |
| Compatible with | NVR, Hybrid DVR, IPCam Plus |
| Compatible with ABUS Link Station | Yes |
| Compatible with Secvest | Yes |
| Compatible with wAppLoxx | Yes |
| Compatible with wAppLoxx Pro | Yes |
| Connections | 1 x RJ45, 1 x DC |
| DC voltage supply | 12 (+/-10 %) V |
| Day/night switching | ICR/Color/B/W |
| Design | Tube |
| Dimensions | (LxWxH) 390x160x160 mm |
| Dynamic range (WDR) | 120 dB |
| Electronic shutter | 1/3 - 1/1000000 s |
| Encryption | HTTPS |
| Focal length | 2.8 mm |
| Frame rate | 1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps |
| Functions | Scene Change Detection |
| Height | 160 mm |
| Horizontal viewing angle | 102 ° |
| ICR day/night function | Yes |
| IP protection class | 67 |
| IR LEDs | Yes |

IP Tube 8 MPx (4K, 2.8 mm)

Art.-Nr. IPCB68515A

Seite 3 von 4

Technical data - IP Tube 8 MPx (4K, 2.8 mm)

| | |
|-------------------------------|--|
| IR range (up to) | 50 m |
| Image enhancement | WDR, BLC, HLC, 3D DNR, Vertical Display |
| Image sensor | 1/2.5" Progressive Scan CMOS |
| LAN network access | RJ45 10M/100M self-adaptive |
| Language of instructions | DE, UK, FR, NL, DK |
| Length | 390 mm |
| Lens | Fix |
| Lens mount | M12 |
| Max. humidity | 95 % |
| Max. operating temperature | 60 °C |
| Max. resolution @ frame rate | 3840 x 2160 @ 20 fps |
| Microphone | No |
| Min. operating temperature | -30 °C |
| Minimum illumination (IR) | 0 lx |
| Minimum illumination (colour) | 0,01 lx |
| Motion detection | 8 zones |
| Net weight | 1,2 kg |
| Network access | RJ45 |
| Network camera protocols | IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ONVIF Profile S, ONVIF Profile G, ABUS Server, Secvest Link |
| Noise reduction | 3D DNR |
| Number of IR LEDs | 10 |
| Number of streams | 3 |
| Number of users | 32 |
| OSD language | DE, UK, FR, NL, DK |
| Other functions | Auto Backup Recording, Secvest Connectivity |
| Pixels (effective) | 3840(H) x 2160(V) pixel |
| PoE standard | IEEE 802.3at |
| Power consumption | 792 mA |
| Private zones | 4 |
| Protection class IK | 10 |
| Resolution | 8 MP |
| Resolution modes | Stream 1: 3.840 x 2.160 @ 20 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1.280 x 720 @ 25 fps |
| Simultaneous network access | 6 |
| Storage medium | microSD card, 256 GB (opt.) |
| Supported browsers | IE10, IE11, Mozilla Firefox 30.0+, Chrome 31.0+ |
| Technology | IP |

IP Tube 8 MPx (4K, 2.8 mm)

Art.-Nr. IPCB68515A

Seite 4 von 4

Technical data - IP Tube 8 MPx (4K, 2.8 mm)

| | |
|------------------------------|---|
| Video Content Analysis (VCA) | Tripwire Detection, Intrusion Detection |
| Video compression | Stream 1: H.264, H.265, Dynamic GOP, Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265, MJPEG |
| Video network bandwidth | 32 kBit/s - 16 MBit/s |
| Video system | IP |
| White balance | AWB, Manual |
| Width | 160 mm |