

# Day/Night Mini Outdoor Camera

Art.-Nr. TVCC40010

Seite 1 von 2

## Unobtrusive monitoring indoors or outdoors

The analogue day/night mini outdoor camera is the ideal supplement to the TWR30004 4-channel recorder and the TVVR30104 video surveillance kit. It stands out with its plain, unobtrusive design and high protection class (IP66), which means it can be used both outdoors and indoors without an additional weatherproof housing. With a high, detailed resolution of 600 TVL, it delivers precise video images for accurate recognition of persons.

## Flexible mounting options

Fast and easy installation is guaranteed with the 20 m combination cable and power supply unit provided.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

## Technologies

- Compact day/night vision mini outdoor camera
- Varied camera installation options - whether indoors or outdoors
- Simple design and high protection class (IP66)
- High detailed resolution, thanks to 600 TVL
- 1 x 20 metre coaxial cable included
- Ideal for extension of TVVR30004 or TVVR30104

## Technical data - Day/Night Mini Outdoor Camera

Aperture at minimum illumination (IR)	0
Aperture at minimum illumination (color)	0,1
Article program	Performance
Backlight compensation	Yes
Camera type	Day/night outdoor camera
Colour	white
Connections	Video signal (BNC), power supply (DC)
Construction type of device	Dome
Current consumption	420 mA
DC power supply	12 V
Day/night switching	Electromechanical IR-cut filter
Depth	150 mm

# Day/Night Mini Outdoor Camera

Art.-Nr. TVCC40010

Seite 2 von 2

## Technical data - Day/Night Mini Outdoor Camera

Diameter	70 mm
Dimensions	150 x 70 mm
Electronic shutter	1/25 ~ 1/15.000 sek.
Focal length	3,6 mm
Height	150 mm
Horizontal viewing angle	68,4 °
IR LEDs	Yes
IR range (up to)	10 m
Image sensor	1/3" DIS
Lens	Fixed
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Min. operating temperature	-20 °C
Minimum illumination (IR)	0 lx
Net weight	0.36 kg
Noise suppression	> 52 dB
PSTI conformity needed	No
Pixels (effective)	720 (H) x 480 (V)
Product group	Video
Protection class IP	66
TVL	600
Video system	PAL / NTSC
WEEE group	09
width	70 mm