

Day/Night Mini Outdoor Dome Camera

Art.-Nr. TVCC34010

Seite 1 von 2

Unobtrusive monitoring indoors or outdoors

The analogue day/night outdoor dome camera is the ideal supplement to the TWR30004 4-channel recorder and the TVVR30104 video surveillance kit. It stands out with its plain design and high protection class (IP66), which means it can be used both outdoors and indoors. The camera has integrated IR LEDs for 24/7 use both day and night. With a high, detailed resolution of 600 TVL, it delivers precise video images for accurate recognition of persons.

Flexible mounting options

Fast and easy installation is guaranteed with the 20 m combination cable and power supply unit provided.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

Technologies

- Compact day/night vision mini outdoor dome camera
- Varied camera installation options - whether indoors or outdoors
- Simple design and high protection class (IP66)
- High detailed resolution, thanks to 600 TVL
- 1 x 20 metre coaxial cable included
- Ideal for extension of TVVR30004 or TVVR30104

Technical data - Day/Night Mini Outdoor Dome Camera

Article program	Performance
Backlight compensation	Yes
Camera type	Day/night outdoor camera
Colour	white
Connections	Video signal (BNC), power supply (DC)
Construction type of device	Dome
Current consumption	420 mA
DC power supply	12 V
Day/night switching	Electromechanical IR-cut filter
Depth	59 mm
Diameter	59 mm
Dimensions	59 x 83 x 90 mm
Electronic shutter	1/25 ~ 1/15.000 sec.
Focal length	3.6 mm

Day/Night Mini Outdoor Dome Camera

Art.-Nr. TVCC34010

Seite 2 von 2

Technical data - Day/Night Mini Outdoor Dome Camera

Height	90 mm
Horizontal viewing angle	68,4 °
IR LEDs	Yes
IR range (up to)	10 m
Image sensor	1/3" DIS
Length	59 mm
Lens	Fixed
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Min. operating temperature	-20 °C
Minimum illumination (IR)	0 lx
Minimum illumination (color)	0.1 lx
Net weight	0.4 kg
Noise suppression	> 52 dB
PSTI conformity needed	No
Pixels (effective)	720 (H) x 480 (V)
Product group	Video
Protection class IP	66
TVL	600
Video system	PAL / NTSC
WEEE group	09
width	83 mm