

Analog HD Tube 2 MPx (1080p, 2.8 mm - 12 mm)

Art.-Nr. HDCC62550

Seite 1 von 3

MONITORING FOR COMPANIES: CLEAR IMAGES, FLEXIBLE TECHNOLOGY, EASY TO INSTALL

ABUS Analogue HD: clear images via coaxial cable

The Analogue HD Tube 2 MPx camera is ideal for surveillance (CCTV) of extensive areas indoors and outdoors. Its high-quality image sensor delivers razor-sharp, smooth and detailed images. Its powerful True WDR function ensures uniform illumination of the surveillance area (foreground and background) in high-contrast lighting situations (e.g. backlighting).

24/7 indoor and outdoor surveillance

The automatic day/night switching of the modern IR LED technology ensures good image illumination in changing light conditions. The IP67 protection class makes the Analogue HD Tube robust in the face of wind and weather.

Easy installation: Motorised zoom, wide range of holders

The camera can be focused remotely via recorder and motorised zoom lens by just one person. The large selection of brackets offers flexibility for every installation location.

Analogue HD technology: ideal for inexpensive retrofitting

The use of existing cabling enables quick and easy retrofitting. Simply swap cameras and recorders and the "old" surveillance system becomes state of the art. Coaxial cables or 2-wire lines that have already been laid can continue to be used. Supported video standards: HD-TVI, HD-CVI, AHD and CBVS/FBAS.

Note: The effective IR range depends on where the camera is used or installed.

Technologies

- 2 MPx resolution: 1920 x 1080 @ 30 fps
 - True WDR effectively compensates for light/dark contrasts
 - Easy installation and focusing via remote access with the motorised zoom lens (2.7 – 13.5 mm)
 - Powerful IR LED technology for improved illumination up to 40 m at night
 - Weatherproof (IP67) for outdoor use
 - 4-in-1 video output (switchable TVI / AHD / CVI / CVBS)
 - Perfect for retrofitting: Transmission using conventional and existing CCTV infrastructure, such as coaxial or 2-wire cables
 - Cable length of up to 500 m possible without loss
 - Wide variety of holders for straightforward, cost-efficient installation
-

Analog HD Tube 2 MPx (1080p, 2.8 mm - 12 mm)

Art.-Nr. HDCC62550

Seite 2 von 3

Technical data - Analog HD Tube 2 MPx (1080p, 2.8 mm - 12 mm)

AC power supply	24 V +/-25 % V
Amplifier control	AGC, 4 level
Aperture at minimum illumination (color)	1.2
Application purpose	General surveillance
Backlight compensation	True WDR
Camera outputs	1 x BNC (HD-TVI), 1 x BNC (FBAS)
Camera type	Tube
Colour	white
Compatible with Secvest	No
Compatible with wAppLoxx	No
Connections	1 x BNC (HD-TVI), 1 x BNC (FBAS), 1 x DC/AC (2-Pin)
Construction type of device	Tube
Current consumption	750 mA
DC power supply	12 V +/-25 % V
Day/night switching	Electromechanical IR cut filter
Digital zoom	Yes
Dimensions	(LxWxH) 270x92x89 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/50 – 1/500000 s
Focal length	2.8 – 12 mm
Height	89 mm
Horizontal viewing angle	32.1 – 103.0 °
Housing material	Metal
IR LEDs	Yes
IR range (up to)	40 m
Image integration	2x - 16x
Image optimization	WDR, BLC, ATW, DNR
Image sensor	1/3" Progressive Scan CMOS
Length	270 mm
Lens	Motorised zoom, autofocus
Lens control	AI
Lens mount	14 mm
Max. Air humidity	90 %
Max. Operating temperature	60 °C
Max. Resolution @ frame rate	1080p @ 25 frames/s (50Hz)/1080p @ 30 frames/s (60Hz)
Microphone	No
Min. operating temperature	-40 °C
Minimum illumination (IR)	0 lx

Analog HD Tube 2 MPx (1080p, 2.8 mm - 12 mm)

Art.-Nr. HDCC62550

Seite 3 von 3

Technical data - Analog HD Tube 2 MPx (1080p, 2.8 mm - 12 mm)

Minimum illumination (color)	0.1 lx
Minimum lighting (B/W)	0.01 lx
Net weight	0.79 kg
Noise suppression	3D DNR
Optical zoom	4.2 x
PSTI conformity needed	No
Pixels (effective)	1920 x 1080
Power consumption	9 W
Privacy zones	8
Product group	Camera
Protection class IP	67
Radio functions	Motion Detection, Tripwire Detection and Intrusion Detection via DVR
Resolution	2MPx
Resolution modes	1920 x 1080
Video channels HD-TVI	1
Video system	HD-TVI
WEEE group	09
White balance	ATW, manual
width	92 mm