

19.5" Full HD LED Monitor

Art.-Nr. TVAC10032

Seite 1 von 2

The 19.5" full HD LED monitor offers sharp images in 16:9 format and is ideal for surveillance projects with an ABUS recorder. High-resolution images are provided via an HDMI cable for precision monitoring. Detailed surveillance pictures in full HD. Thanks to a rapid reaction time of just 5 ms, surveillance pictures are transmitted in a matter of seconds. Quick movements on the screen are shown clearly and continuously, without any distortions, flickering or ghost images. You see meaningful, reliable pictures in full HD quality. Versatile connections The video monitor can be connected to a recorder or PC. Thanks to the HDMI connection, the monitor is optimally suited to displaying images in full HD. An additional VGA and a DVI connection make the monitor a highly flexible component in a wide range of surveillance systems, and it is further equipped with an integrated loudspeaker and an audio input and output. Energy efficiency for continuous monitoring The efficient LED display ensures very low power consumption - ideal for continuous use. Surveillance monitor for wall or ceiling Fast mounting with VESA standard mounts: The monitor can be fixed to the wall or to the ceiling as per your requirements.

Technologies

- Full HD resolution: 1920 x 1080 pixels
- Fast reaction time (5 ms) for flowing images
- LED backlighting: Brilliant colour display and high contrast
- Picture-in-picture display for more information at a glance
- Connections: HDMI, DVI, VGA, audio input and output
- Integrated loudspeakers
- Low power consumption for long-term monitoring (LED technology)
- Wall and ceiling installation possible (with VESA mount)

Technical data - 19.5" Full HD LED Monitor

Brightness	250
Colour	black
Comb filter	3D
Connection type	1x VGA,1xDVI,1xHDMI, 1x Audio
Contrast ratio	1000:01
Current consumption	2,000 mA
DC power supply	12 V
Depth	41 mm
Dimensions	(WxHxD) 470x360x45 mm
Display surface	matte
Gross weight	3.3 kg
Height	360 mm
Housing material	Plastic
Image format	16:09

19.5" Full HD LED Monitor

Art.-Nr. TVAC10032

Seite 2 von 2

Technical data - 19.5" Full HD LED Monitor

Language OSD	multilingual
Length	41 mm
Loudspeaker	2
Max. Air humidity	70 %
Max. Operating temperature	50 °C
Max. number of video feeds	3
Min. operating temperature	0 °C
Monitor type	Standard TFT
Net weight	2.38 kg
PSTI conformity needed	No
Power consumption	23 W
Product group	Accessories
Response time	5 ms
Screen diagonal	19.5 in
Signal detection	Automatic
Viewing angle horizontal/vertical	75/80
WEEE group	09
width	470 mm