

IP Mini Dome 2 MPx (1080p, 2.8 mm)

Art.-Nr. IPCB42510A

Seite 1 von 3

Technical data - IP Mini Dome 2 MPx (1080p, 2.8 mm)

Alarm generation	E-Mail, NAS, FTP
Aperture at minimum illumination (color)	F1.6
Application purpose	General surveillance
Article program	Professional
Backlight compensation	WDR, BLC, HLC
Camera type	Mini Dome
Colour	RAL9003
Compatible with	NVR, Hybrid DVR, IPCam Plus
Compatible with ABUS Link Station	Yes
Compatible with Secvest	Yes
Compatible with wAppLoxx	Yes
Compatible with wAppLoxx Pro	Yes
Connections	1 x RJ45, 1 x DC
Construction type of device	Dome
Current consumption	625 mA
DC power supply	12 (+/-10 %) V
Day/night switching	ICR/Color/B/W
Dimensions	(LxWxH) 97x100x53 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/3 - 1/100000 s
Encryption	HTTPS
Focal length	2,8 mm
Frame rate	1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps
Height	53 mm
Horizontal viewing angle	108 °
ICR day/night function	Yes
IR LEDs	Yes
IR range (up to)	10 m
Image optimization	WDR, BLC, HLC, 3D DNR, Vertical Display
Image sensor	1/2.8" Progressive Scan CMOS
Language Manual	DE, UK, FR, NL, DK
Language OSD	DE, UK, FR, NL, DK
Length	97 mm

IP Mini Dome 2 MPx (1080p, 2.8 mm)

Art.-Nr. IPCB42510A

Seite 2 von 3

Technical data - IP Mini Dome 2 MPx (1080p, 2.8 mm)

Lens	Fixed
Lens mount	M12
Max. Air humidity	95 %
Max. Operating temperature	60 °C
Max. Resolution @ frame rate	1920 x 1080 @ 30 fps
Microphone	No
Min. operating temperature	-30 °C
Minimum illumination (IR)	0 lx
Minimum illumination (color)	0.009 lx
Motion detection	8 zones
Net weight	0.42 kg
Network bandwidth Video	32 kBit/s - 16 MBit/s
Network camera protocols	IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ABUS Server
Network connection	RJ45
Network connection LAN	RJ45 10M/100M self-adaptive
Noise suppression	3D DNR
Number of IR LEDs	10
Number of streams	3
Number of users	32
ONVIF	Profile G, S, T
Other functions	Auto Backup Recording, Secvest Connectivity
PSTI conformity needed	No
Pixels (effective)	1920(H) x 1080(V)
PoE Standard	IEEE 802.3af
Power consumption	9.5 W
Privacy zones	4
Product group	Camera
Protection class IK	8
Protection class IP	66
Radio functions	Scene Change Detection
Resolution	2 MP
Resolution modes	Stream 1: 1.920 x 1.080 @ 25 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1.920 x 1.080 @ 25 fps
Simultaneous network access	6
Storage medium	microSD card, 256 GB (opt.)
Supported browsers	IE10, IE11, Mozilla Firefox 30.0+, Chrome 31.0+
Vertical angle of view	59 °
Video Content Analysis (VCA)	Tripwire Detection, Intrusion Detection

IP Mini Dome 2 MPx (1080p, 2.8 mm)

Art.-Nr. IPCB42510A

Seite 3 von 3

Technical data - IP Mini Dome 2 MPx (1080p, 2.8 mm)

Video compression	Stream 1: H.264, H.265, Dynamic GOP, Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265, MJPEG
Video system	IP
WEEE group	09
White balance	AWB, Manual
width	100 mm