

86TI/45 without cylinder

Seite 1 von 2



INTEGRATION INTO LOCKING SYSTEMS

Our 86 Titalium™ can easily be integrated into existing locking systems.

Systematically secure your control cabinets, doors, gates, lockers, or sheds against break-in attempts with this robust padlock. The solid lock body is made of TITALIUM™ special aluminum, the hardened steel shackle is equipped with NANO PROTECT™ coating. The lock comes without a lock cylinder. Commercially available Euro profile half cylinders can be installed in the padlock using a conventional Allen key so that it can be integrated into existing locking systems.

Technologies

- Solid lock body made from TITALIUM™ aluminium alloy - high security with low weight
- Hardened steel shackle with NANO PROTECT™ plating for extreme corrosion resistance
- Customary EURO-cylinders can be integrated easily without special tools
- Double bolted shackle
- Possible to integrate into keying systems
- 86TI/55: Key retaining or automatic locking (depending on position of cam)
- 25°: Automatic locking (only for adjustable strike plates)
- 45°: Key-retaining
- 86TI/45: Key retaining

Operation and use

- To secure valuables/ goods of greater value or at a high risk of theft
- To secure doors, gates, cupboards, tool boxes, cellar windows, sheds, switchboards, etc.

86TI/45 without cylinder

Variants

- Sizes: 45 and 55 mm
- IB: with stainless steel shackle (45mm only)

Technical data - 86TI/45 without cylinder

Depth e	27 mm
Height f	96,5 mm
Horizontal clearance b	26,5 mm
Keyed alike	Yes
Locking type	key
Security Level Home Security	7
Security card	No
Shackle diameter d	8 mm
Vertical clearance c	32,5 mm
Weight [g]	185 g
Width a	46,5 mm
colour	aluminum
type of cylinder	without cylinder
EAN	4003318277788

Technical drawing

