

# ABUS IP video surveillance 2MPx Wi-Fi mini tube camera

Art.-Nr. TVIP62560

Seite 1 von 2

## Technical data - ABUS IP video surveillance 2MPx Wi-Fi mini tube camera

Alarm generation	Email
Aperture	F2.0
Automatic aperture control	No
Base event	Motion detection
Channel width	20 MHz
Colour	white
Compatible with	TVVR36xxx / TVVR33xxx / NVRxxxxx
Compatible with Secvest	Yes
Compatible with Smartvest	No
Compatible with wAppLoxx	Yes
Construction type of device	Tube
DC power supply	12 V
Day/night switching	Auto / Manual / Schedule
Dimensions	( $\emptyset$ x L) 70 x 157 mm
Encryption	64/128-bit WEP / WPA/WPA2 / WPA-PSK/WPA2-PSK / WPS
Focal length	2,8 mm
Frequency range	2,4 - 2,4835 GHz
Gross weight	0.778 kg
Horizontal viewing angle	85 °
Housing material	Metal / Plastic
IR LEDs	Yes
IR range (up to)	20 m
IR swivel filter	Yes
Image optimization	BLC / Digital WDR
Image sensor	1/2.8" CMOS
Image settings	Brightness / Contrast / Saturation / Sharpness / Mirroring
Language OSD	DE / UK / FR / NL / DK / IT / PL / ES / SE
Lens mount	M12
Loudspeaker	No
Max. Air humidity	95 %
Max. Operating temperature	60 °C
Max. Resolution @ frame rate	1920 x 1080 @ 25/30 fps
Microphone	No
Min. humidity	10
Min. operating temperature	-30 °C
Minimum illumination (IR)	0 lx

# ABUS IP video surveillance 2MPx Wi-Fi mini tube camera

Art.-Nr. TVIP62560

Seite 2 von 2

## Technical data - ABUS IP video surveillance 2MPx Wi-Fi mini tube camera

Minimum illumination (color)	0.028 lx
Net weight	0.384 kg
Network connection	1x RJ-45 10/100 Mbit/s self-adaptive Ethernet Anschluss
Network connection WLAN	IEEE802.11b/g/n / 11b @ 11Mbit/s / 11g @ 54Mbit/s / 11n @ 150Mbit/s
Network protocols	TCP/IP / ICMP / HTTP / HTTPS / FTP / DHCP / DNS / DDNS / RTP / RTSP / RTCP / PPPoE / NTP / UPnP / SMTP / IPv6
Noise suppression	3D DNR
Number of users	32
Optical wavelength	850
PSTI conformity needed	No
PoE Standard	802.3af
Power consumption	5.8 W
Privacy zones	4
Protection class IP	67
Radio range	(Depending on installation) 20 - 50 m
Recording modes	Manual / time schedule / motion detection
Resolution modes	1920 x 1080 / 1280 x 960 / 1280 x 720 @ 25/30 fps
Sensitivity	11b: -90dBm / 11g: -75dBm / 11n: -74dBm
Software	IPCam Plus (iOS & Android) / iDVR Plus (iOS & Android) / IP Installer
Storage medium	MicroSD (max. 128GB) / NAS
Supported browsers	Internet Explorer, Edge, Chrome, Firefox, Safari
Transmission power	11b: 17 +/- 1,5dBm / 11g: 14 +/- 1,5dBm / 11n: 12,5 +/- 1,5dBm
User levels	3
Video compression	H.264 / MJPEG
WEEE group	09
White balance	Auto white balance (AWB) / incandescent lamp / warm light / natural light / fluorescent lamp