



The new 7" Universal Test Monitor is the ideal helper for all video projects. Conveniently transportable and with a battery life of up to 10 hours, the monitor delivers the desired measurement data everywhere - to video image, network, voltage and cable. In addition to the handy design, the combination of touchscreen and control buttons makes the test monitor particularly user-friendly. The test monitor is Android-based, acts like an ordinary Android tablet and becomes your mobile computer. Designed specifically for the maintenance and installation of IP network cameras, analog TVI, CVI, AHD and CVBS cameras, it offers many more with preinstalled applications:

A network tool with IP address search or PING and PoE measurement function and much more is available for the installation and configuration of IP networks.

Use the test monitor as a mobile power supply for your device, whether directly via PoE with up to 24 W, one of the two 12V and up to 3A plug connectors, or the USB interface with 5V and up to 2A. The latter is ideal for charging your smartphone.

An HDMI input and output make the test monitor even more versatile.

Use the cable tester to check the wiring and length of network cables or to detect damage.

Create snapshots and video sequences to document your installation.

You always have your important documents in digital form with you or simply create them with the familiar Android Office programs.

Increase your productivity by installing your familiar and popular Android applications on your Universal Test Monitor.

An integrated LED lamp helps you to work in poorly lit environments.

The range of functions of the 7" Universal Test Monitor makes it an essential tool for installers and technicians, which you no longer want to miss.

Note: System language is English.

Teknologier

- Universal testskærm til vedligeholdelse og installation af IP netværkskameraer samt analoge TVI-, CVI-, AHD- og CVBS-kameraer
- Høj opløsning 7" touch display med 1.280 x 800 pixels
- Understøtter 4K H.264 og 4K H.265 strømme
- Kompatibel med tredjeparts producenter

- Med netværkssværktøjer til at opretholde og verificere netværket
- Integreret PoE-strømforsyning med 24 W på LAN-porten
- Integreret mobil strømforsyning til enheder og integreret USB-strømforsyning til USB-enheder
- Wi-Fi og Wi-Fi hotspot funktion
- Med kabel tester til kontrol af netværksskabler
- Data backup på SD-kort muligt (screenshots / videoer / dokumenter)

Tekniske oplysninger - 7" Testskærm

Batteri - type	7,6 V / 7800 mAh, Li-ion Polymer
Bredde	231 mm
Højde	172 mm
Højtaler	Ja
Længde	52 mm
Maks. driftstemperatur	50 °C
Min. driftstemperatur	-10 °C
Monitortype	IPS touch display
Mål	(B x H x D) 231 x 172 x 52 mm
Nettovægt	0,945 kg
OSD-sprog	GB, FR, IT
Opløsnings tilstand	1280 x 800
Skærmdiagonal	7 in
Sprog, vejledning	DE, GB
Spændingsforsyning DC	12 V
Strømforbrug	2.000 mA
Tilslutninger	1 x HDMI-indgang, 1 x HDMI-udgang, 1 x BNC-indgang (TVI, CVI, AHD, CVBS), 1 x BNC-indgang (SDI), 1 x BNC-udgang (CVBS), 1 x RJ45), 2 x RJ45 (PSE-indgang), 1 x RJ45 (UTP-port), 1 x 3,5 mm jack (lydindgang), 1 x 3,5 mm jack (lydudgang), 1 x DC Indgang (12 V, 2 A), 2 x DC-udgang (12 V, 3 A), 1 x USB-udgang (5 V, 2 A), 1 x RS485
Videosystem	IP, TVI, CVI, AHD, CVBS