

VdS Surface Mount Panic Alarm Button

Art.-Nr. AZ6500

Seite 1 von 2



If you press the panic button, you trigger a silent alarm to call for help. You can use the panic button as a standalone device or integrate it into the burglar alarm system. The button is tamper-monitored. For panic and tamper alarms, you have an NO or NC contact. The panic button is VSÖ and VdS C certified.

Technologies

- Simple surface mounting
- Inconspicuous, discreet alarm signalling
- Certified VdS Class C

Technical data - VdS Surface Mount Panic Alarm Button

Certifications	VdS-C
Compatible with	Secoris, Secvest, Terxon
Connections	1 x NO/NC alarm contact; 1x NO/NC tamper contact
Depth	47 mm
Dimensions	(WxHxD) 85x85x47 mm
Height	85 mm
Housing material	ABS
IP protection class	32
Installation location	Surface or flush fitting
Length	47 mm
Max. operating temperature	55 °C
Net weight	0,18 kg
PSTI conformity required	No
Sabotage monitoring	Yes
Switching outputs	Maximum switching power: 3 A/75 V

VdS Surface Mount Panic Alarm Button



Security Tech Germany

Art.-Nr. AZ6500

Seite 2 von 2

Technical data - VdS Surface Mount Panic Alarm Button

Switching power	225 W
VdS approval no.	G 192028
VdS class	C
Width	85 mm