

Secvest 2WAY Wireless Keypad

Art.-Nr. FU8110

Seite 1 von 2



The Secvest 2WAY wireless keypad is an optional accessory for the Secvest 2WAY. You can operate your system from any wireless keypad using your PIN code. If the wireless keypad is supplied externally with 12V, arming and disarming by proximity chip key is also possible. Up to 4 control units can be integrated into the alarm system. Arranged in various parts of your building, these expansion modules guarantee additional convenience. The Secvest 2WAY can be armed or disarmed directly on the wireless keypad, without having to go back to the central alarm panel each time. Entering an additional code becomes redundant. The four buttons are programmed on the central Secvest 2WAY alarm panel. In addition to the internal arming or the arming of individual sub-sections, you can also activate an output via this keypad, e.g. the garage door. Due to protection class IP54, you can also use the wireless keypad outdoors.

Technologies

- For arming/disarming the alarm panel
- Integrated proximity key fob reader with optional external power supply
- Possible to switch outputs
- Power supply via battery and external source (12 V)
- Power supply using batteries and external power supply (12 V)
- LEDs for displaying the current system status

Technical data - Secvest 2WAY Wireless Keypad

Battery - max. battery life	2 y
Battery - type	3 V CR2 lithium battery
Certifications	INCERT, F&P, NCP
Connections	12V switch terminal, battery compartment
DC voltage supply	3/12 V
Dimensions	(WxHxD) 135x135x30 mm
Environmental class	II

Secvest 2WAY Wireless Keypad

Art.-Nr. FU8110

Seite 2 von 2

Technical data - Secvest 2WAY Wireless Keypad

Height	135 mm
Housing material	ABS
IP protection class	54
Installation location	Indoors and protected outdoor areas
Length	30 mm
Max. humidity	94 %
Max. operating temperature	55 °C
Max. receiving range (building)	30 m
Max. receiving range (free field)	100 m
Max. transmission range (building)	30 m
Max. transmission range (free field)	100 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0,3 kg
PSTI conformity required	No
Radio frequency	868,662 MHz
Radio power	10 mW
Sabotage monitoring	Yes
Security level	2
Voltage monitoring	Yes
Width	135 mm