

Secvest IP Basic Set

Art.-Nr. FUAA10021

Seite 1 von 5



Technologies

- The perfect start with networked alarm technology
- Motion detector for interior room security
- Opening detector for window or door monitoring
- Remote control with active feedback for greater comfort and security
- Fast notification by VoIP voice message call in case of an alarm
- Suitable for protecting apartments and small properties

Technical data - Secvest IP Basic Set

Net weight	3.2 kg
PSTI conformity needed	No
Product group	Alarm panel
WEEE group	09

Technical data - Secvest IP Wireless Alarm Control Panel

Access protection	User name, password
Active intrusion protection	With mechatronic components (jimmying attempt monitoring only in the active state)
Alarm generation	E-mail, VoIP (landline, cellular communication, VoIP client) and push notification
Battery type	12 V, 1.2 Ah
Communication/ Alarm	email
Current consumption	1,200 mA
DC power supply	13,8 V
DSL monitoring	Yes
Dimensions	(WxHxD) 193x233x45 mm
Display type	Status LEDs

Secvest IP Basic Set

Art.-Nr. FUAA10021

Seite 2 von 5

Technical data - Secvest IP Wireless Alarm Control Panel

Duplex antenna technology	Yes
Emergency power supply	Yes
Environmental class	II
Event memory	Yes
Expandable (radio)	Yes
Gross weight	2.56 kg
Height	233 mm
Housing material	ABS
Integrated siren	No
Language Manual	12 V, 1.2 Ah
Language OSD	DE, UK, FR, NL, DK
Language Packaging	DE, UK, FR, NL, DK
Length	45 mm
Max. Air humidity	75 %
Max. Emergency power runtime	5 h
Max. Operating temperature	55 °C
Max. Receive range (building)	30 m
Max. Receive range (free field)	100 m
Max. Transmit range (free field)	100 m
Max. Transmitting range (building)	30 m
Min. operating temperature	0 °C
Modulation	FM
Mounting location	With surrounding conditions optimally adjusted for wireless performance
Net weight	2.137 kg
Network connection	RJ-45 Ethernet 10/100 Base-T
Network protocols	TCP/IP, DHCP, SMTP, DNS, NTP, HTTP
Number of events	500
Number of operating elements	3
Number of remote controls	3
Number of users	2
Number of virtual IP zones	3
Number of wireless zones	3
Operating mode	Local: via Secvest Key, wireless remote control, wireless additional door lock; remote: online via web interface, iPhone/iPad app
Outputs	1xrelay, 4xtransistor

Secvest IP Basic Set

Art.-Nr. FUAA10021

Seite 3 von 5

Technical data - Secvest IP Wireless Alarm Control Panel

PSTI conformity needed	No
Power consumption	13.8 W
Power supply unit	External
Product group	Alarm panel
Programming 1	Via integrated seb-server
Protection class IP	34
Radio alarm bandwidth	Narrow band
Radio frequency	868.66 MHz
Radio power	10 mW
Remote maintenance	Yes
Security level	Reverse polarity protection
Sub-areas/monitoring areas	1
Supported browsers	Safari 5, Mozilla Firefox 5, Google Chrome, Internet Explorer 9
Switching outputs	7
Tamper monitoring	Yes
VdS class	without
Video verification	Optional with PIR network camera
Voltage monitoring	Yes
WEEE group	09
width	193 mm
EAN	4043158029291

Technical data - Secvest Wireless Magnetic Contact CC (white)

Battery - max. battery life	2 years(s)
Battery type	3 V CR2 Li/MnO ₂
Certifications	VdS home, EN 50131 Grade 2
Color options	white, brown
Colour	white
Compatible with	Secvest, Terxon, BUM060040
Connections	Screw terminal (CC)
Current consumption	30 mA
DC power supply	3 V
Detection method	Magnetic field measurement
Dimensions	(WxHxD) 33x89x29 mm
Environmental class	I
Height	89 mm
Housing material	ABS
Length	29 mm
Max. Operating temperature	55 °C
Max. Transmit range (free field)	100 m

Secvest IP Basic Set

Art.-Nr. FUAA10021

Seite 4 von 5

Technical data - Secvest Wireless Magnetic Contact CC (white)

Max. Transmitting range (building)	30 m
Mechanical protection	No
Min. operating temperature	-10 °C
Modulation	FM
Mounting location	Windows, doors
Net weight	0.076 kg
PSTI conformity needed	No
Power consumption	0.09 W
Product group	Detectors
Radio frequency	868.6625 MHz
Radio networked	Yes
Radio power	10 mW
Security gradient	2
Sensor type	Reed contact
Status display	Yes
Tamper monitoring	Yes
Technology	Electronics
Type of protection	Intrusion protection
VdS approval no.	H 110004
VdS class	Other
Voltage monitoring	Yes
WEEE group	09
Width sensor	33 mm
width	33 mm
EAN	4043158057652

Technical data - Secvest Wireless Remote Control

Battery - max. battery life	2 years(s)
Battery type	CR2450 3V Li-Mn (FU2987)
Certifications	VdS (H 114001)
DC power supply	3 V
Display type	LED
Environmental class	II
Height	17 mm
Housing material	ABS
Language Manual	DE, UK, FR, NL, DK, PL
Language Packaging	DE, UK, FR, NL, DK, PL, ES, SE, IT
Length	62 mm
Max. Air humidity	75 %

Technical data - Secvest Wireless Remote Control

Max. Operating temperature	40 °C
Max. Receive range (building)	30 m
Max. Receive range (free field)	200 m
Max. Transmit range (free field)	200 m
Max. Transmitting range (building)	30 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0.026 kg
PSTI conformity needed	No
Product group	Operation
Radio frequency	868 MHz
Radio power	10 mW
Security gradient	2
Technology	Electronics
Voltage monitoring	Yes
WEEE group	09
width	36 mm
EAN	4043158058512