

Wireless Smoke Alarm Device (RM40)

Art.-Nr. HSRM20000

Seite 1 von 2

The optical VdS wireless smoke alarm device reacts to visible fire smoke within its detection range. If an alarm detects smoke particles in the air, all alarms in the building are triggered. The wireless smoke alarm device is installed on the ceiling. Minimum distances to the wall (15 cm), corners (50 cm), etc., must be observed (for details see the user guide). We recommend a separate detector for each hallway, staircase, living room, and bedroom. If a detector detects smoke, the piezo sounder emits an alarm which is 85 dB loud - from all detectors at the same time. The detector that first detected the smoke can be identified by an alarm tone that is different from the others. CRLF CRLF up to 32 smoke detectors can be networked wirelessly - each with a range of up to 30 m (additional wireless modules are not required). The cascading of the detectors guarantees a high level of safety; an alarm is passed across the entire chain from the first to the last detector. The effective range does however depend on the structural characteristics (a wireless test is recommended before installation). The batteries recommended have a lifespan of up to 2 years. The detector reports a weak battery by emitting regular beeps. We recommend that the detector be tested once per month. The detector is VdS-certified thanks to the high level of safety and reliability it provides.

Technologies

- Optical smoke detector with integrated piezo alarm sounder
- Detectors can be integrated in a wireless network which could contain 32 detectors
- Reliable warning of life-threatening smoke formation
- Detector cascading for greater safety and coverage
- Clearly visible status LED

Technical data - Wireless Smoke Alarm Device (RM40)

Battery - max. battery life	2 years(s)
Battery type	9 V battery (lithium)
Certifications	EN 14604:2005/AC:2008
Current consumption	40 mA
DC power supply	9 V
Detection area of detector (m ²)	40 m ²
Detection method	Photoelectric reflection
Dimensions	(HxD) 35x102 mm
Display type	LED
Gross weight	0.19 kg
Height	35 mm
Housing material	ABS
Language Manual	DE, UK, FR, IT, NL, DK
Language Packaging	DE, UK, FR, IT, NL, DK, SE, PL, ES
Max. Air humidity	90 %

Wireless Smoke Alarm Device (RM40)

Art.-Nr. HSRM20000

Seite 2 von 2

Technical data - Wireless Smoke Alarm Device (RM40)

Max. Operating temperature	40 °C
Max. Receive range (building)	30 m
Max. Transmitting range (building)	30 m
Min. operating temperature	0 °C
Mounting location	Ceiling
Net weight	0.129 kg
PSTI conformity needed	No
Radio frequency	868 MHz
Sound pressure	85 dB
Status display	Yes
Voltage monitoring	Yes
WEEE group	09
width	102 mm