

HD-SDI Repeater

Art.-Nr. TVAC22010

Seite 1 von 1



This HD-SDI repeater is used to extend the transmission distance of HD-SDI signals. The transmission distance can be extended by up to 150 meters (depending on the cable quality).

Technologies

- Extends the range of HD-SDI signals
- Max. range increase: 150 m (RG6 cable), 80 m (RG59 cable)
- Status LED for signal quality

Technical data - HD-SDI Repeater

Certifications	CE
DC voltage supply	6 – 15 V
Data input	720p50, 720p60, 1080i50, 1080i60, 1080p24, 1080p25, 1080p30, 1080p50, 1080p60, 2K (2048 x 1080) MB/s
Dimensions	63,6 x 70 x 26 mm
Gross weight	0,4 kg
Height	26 mm
Input	1 x HD-SDI (SMPTE 259M, SMPTE 292M, SMPTE 494M/495M)
Language of instructions	DE, UK, FR, NL, DK, PL
Length	70 mm
Max. humidity	85 %
Max. operating temperature	50 °C
Min. operating temperature	0 °C
Net weight	0,32 kg
Output	1 x HD-SDI (SMPTE 259M, SMPTE 292M, SMPTE 494M/495M)
Power consumption	500 mA
Transmission distance	150 m
Width	63,6 mm