



## Technologies

- Wireless main unit with 7" color LCD monitor for reception of video and audio data of the Eycasa components in indoor areas
- Secure, digital wireless transmission
- Control of the complete door intercom application: See, hear, speak, and open the door
- Operation via touchscreen display
- Management of event lists
- Choice between wall or table mounting
- Display of up to four cameras at once
- Automatic switching of the views depending on the event
- Software can be upgraded via integrated SD card slot
- Memo board for short notes

## Technical data - Eycasa Main Unit

|                          |                         |
|--------------------------|-------------------------|
| Adjustable alarm tone    | 5 doorbell tones        |
| Audio data rate          | 0,064                   |
| Audio frequency          | 1,9 GHz                 |
| Audio modulation         | TMDA                    |
| Audio sensitivity        | -82                     |
| Audio transmission power | 20                      |
| Connectible devices      | Eycasa main unit        |
| DC voltage supply        | 12 V                    |
| Event memory             | 500                     |
| Fastening                | Table mount, wall mount |
| Height                   | 200 mm                  |

# Eycasa Main Unit



Security Tech Germany

Art.-Nr. CASA30200

Seite 2 von 2

## Technical data - Eycasa Main Unit

|                            |   |
|----------------------------|---|
| IP protection class        | 30                                      |
| Length                     | 100 mm                                  |
| Loudspeaker                | 8 Ohm, 2 W x 2                          |
| Max. operating temperature | 50 °C                                   |
| Microphone                 | Yes                                     |
| Min. operating temperature | -10 °C                                  |
| Monitor                    | 7" touchscreen LCD                      |
| Net weight                 | 0,67 kg                                 |
| Network access             | RJ45                                    |
| Number of channels         | 4                                       |
| Power consumption          | 800 mA                                  |
| Resolution                 | 800 x 600                               |
| Storage medium             | SDHC card, max. 32 GB                   |
| Video data rate            | 2                                       |
| Video frequency            | 2,4 GHz                                 |
| Video modulation           | FHSS+GFSK                               |
| Video sensitivity          | -82                                     |
| Video transmission power   | 13,5                                    |
| Width                      | 185 mm                                  |
| Wireless range             | 30 m (depending on site conditions) * m |