



## Technologies

- Wireless main unit with 7" color LCD monitor for reception of video and audio data of the Eycasa components in indoor areas
- Secure, digital wireless transmission
- Control of the complete door intercom application: See, hear, speak, and open the door
- Operation via touchscreen display
- Management of event lists
- Choice between wall or table mounting
- Display of up to four cameras at once
- Automatic switching of the views depending on the event
- Software can be upgraded via integrated SD card slot
- Memo board for short notes

## Technical data - Eycasa Main Unit

Adjustable alarm tone	5 doorbell tones
Audio data rate	0,064
Audio frequency	1,9 GHz
Audio modulation	TMDA
Audio sensitivity	-82
Audio transmission power	20
Connectible devices	Eycasa main unit
DC voltage supply	12 V
Event memory	500
Fastening	Table mount, wall mount
Height	200 mm

# Eycasa Main Unit



Security Tech Germany

Art.-Nr. CASA30200

Seite 2 von 2

## Technical data - Eycasa Main Unit

IP protection class	30
Length	100 mm
Loudspeaker	8 Ohm, 2 W x 2
Max. operating temperature	50 °C
Microphone	Yes
Min. operating temperature	-10 °C
Monitor	7" touchscreen LCD
Net weight	0,67 kg
Network access	RJ45
Number of channels	4
Power consumption	800 mA
Resolution	800 x 600
Storage medium	SDHC card, max. 32 GB
Video data rate	2
Video frequency	2,4 GHz
Video modulation	FHSS+GFSK
Video sensitivity	-82
Video transmission power	13,5
Width	185 mm
Wireless range	30 m (depending on site conditions) * m