

16-Channel Hybrid Digital Recorder 290 Mbit/s (50/240)

Art.-Nr. TVVR60011

Seite 1 von 2



Professional solution for video recording: With up to 8 HD network cameras and 8 analog SD cameras in a single system. This makes the recorder a versatile, professional system with maximum efficiency and return on investment.

Flexible and cost-effective hybrid recording

The hybrid function allows combined operation of the latest HD network cameras (2.0 MPix) and analog SD cameras (resolution: 0.3 MPix). This guarantees cost-effectiveness and return on investment, for example when converting and upgrading existing CCTV systems.

Real-time recording at full resolution

Users can record all channels at full resolution in real time with the HDR plus - for maximum precision and detail in the video data. Especially when recording fast-moving scenes (for example in casinos), this is a precondition for accurate images - because each frame might contain crucial evidence.

User-friendly video surveillance and a perfect overview

The HDR plus has all the functional and equipment features of the HDR series. One of the highlights is the user-friendly recorder software, whose main menu on the HDR plus also features an overview showing all the main camera and network settings.

Mobile access via app

Users can view video images using the ABUS iDVR iPhone app. They can then access all the cameras connected to the HDR plus, wherever they are. Moving PTZ cameras can be controlled, up to 15 recorders can be configured, and up to 4 cameras can be viewed simultaneously.

Quick and easy installation

The recorder can be quickly and simply installed and put into operation using the setup wizard.

Technologies

16-Channel Hybrid Digital Recorder 290 Mbit/s (50/240)

Art.-Nr. TVVR60011

Seite 2 von 2

-
- Connect up to 8 ABUS IP cameras (HD1080p)+ 8 analogue cameras
 - Real-time recording (25 fps) at full camera resolution
 - Well-organised main menu with a clear view of all settings and parameters
 - Up to 8 SATA hard disk drives can be connected
 - Redundant data recording (for protection against data loss)
 - Simple installation with the installation wizard
 - Integrated HDMI and VGA output
 - Status LED indicates recorder status
 - Max. 16 alarm inputs
-