

Terxon SX Complete Package

Art.-Nr. AZ4301

Seite 1 von 4



Technologies

- Wired alarm system with full range of accessories for optimum protection
- Includes control panel, outdoor siren, 2 motion detectors, 5 opening detectors and 50 m alarm cable
- External key switch with cylinder and 5 proximity chip stickers
- Can be flexibly extended at any time
- With eight freely configurable zones

Technical data - Terxon SX Complete Package

Dimensions	170 x 510 x 430 mm
Event memory	Yes

Technical data - Terxon SX Alarm Control Panel

AC voltage supply	230 V
Backup power supply	1
Battery - type	12V DC, 7.0 Ah lead rechargeable battery
Certifications	INCERT
Communication/alarm	Only compatible via external dialer: AZ6301, AZWG10020
Connections	230 V screw terminal, 13.8 V screw terminal, loudspeaker, zone-screw terminal, 11 x switching outputs
Dimensions	(WxHxD) 240x240x85 mm
Display	Two-line LCD alphanumerical display
Environmental class	II
Event memory	Yes
Expandable (hybrid)	No
Fuse	230 V / 250 mA; 12 V: 1 A fast; battery: 2 A fast
Height	240 mm
Housing material	Alarm centre: Metal, control unit: ABS
Integrated siren	Yes
Length	85 mm
Max. backup power supply duration	12 h

Terxon SX Complete Package

Art.-Nr. AZ4301

Seite 2 von 4

Technical data - Terxon SX Alarm Control Panel

Max. battery charging time	24 h
Max. humidity	75 %
Max. number of control units	4
Max. operating temperature	40 °C
Min. operating temperature	-10 °C
Net weight	2,45 kg
Number of control units	4
Number of events	250
Number of sabotage zones	1
Number of users	16
Number of wired zones	8
OSD language	11 selectable languages
PSTI conformity required	No
Power consumption	200 mA
Programming 1	Via control panel
Remote configuration	No
Sabotage lines	2
Sabotage monitoring	1
Security level	2
Sub-areas/monitoring areas	4
Switching outputs	3 x 500 mA transistors, 8 x 50 mA transistors, freely programmable
Voltage monitoring	Yes
Width	240 mm
Zone closure	NC, DEOL
EAN	4043158015690

Technical data - VdS Battery, 12 V, 7.2 Ah

Battery type	Lead gel
Capacity	7,2
Certifications	VdS
Charging cycles	up to 1000
DC voltage supply	12 V
Dimensions	(WxHxD) 65x94x151 mm
Height	94 mm
Length	151 mm
Net weight	2,54 kg
PSTI conformity required	No
VdS approval no.	G 112110
Width	65 mm
EAN	4043158000634

Terxon SX Complete Package

Art.-Nr. AZ4301

Seite 3 von 4

Technical data - Surface Mount Key-Switch

Compatible with	Secoris, Secvest, Terxon
DC voltage supply	10-15 V
Dimensions	(WxHxD) 114x85x42 mm
Height	85 mm
Housing material	ABS
IP protection class	55
Installation location	Surface fitting
Length	42 mm
PSTI conformity required	No
Power consumption	2 mA
Sabotage monitoring	Yes
Status display	Yes (2 LEDs)
Width	114 mm
EAN	4012270001461

Technical data - Screw Terminal Distributor Flush Mount, 12-pins (white)

Colour	white
Connections	12 screw connections
Dimensions	(WxHxD) 65x65x25 mm
Height	65 mm
Housing material	ABS
Installation location	Surface mounting
Length	25 mm
PSTI conformity required	No
Sabotage monitoring	Yes
Width	65 mm
EAN	4043158053012

Technical data - Optic/Acoustic Combination Signal Transmitter

DC voltage supply	12 V
Dimensions	(WxHxD) 190x310x115 mm
Flashing frequency	1,17 Hz
Height	310 mm
Housing material	Aluminium
IP protection class	34
Installation location	Indoors and outdoors
Length	115 mm
Light source	Xenon
Luminous colour	Red
Max. operating temperature	55 °C

Terxon SX Complete Package

Art.-Nr. AZ4301

Seite 4 von 4

Technical data - Optic/Acoustic Combination Signal Transmitter

Min. operating temperature	-25 °C
PSTI conformity required	No
Power consumption	340 mA
Sabotage monitoring	Yes
Sound pressure	110 dB
Width	190 mm
EAN	4043158008333

Technical data - Wired NC Opening Detector (white)

Cable length	2 m
Cable type	2-core
Colour	white
Connections	NC, max. contact capacity 100 V/5 W/0.05 A
Dimensions	(WxHxD) 11x12x48 mm
External field protection	No
Height	12 mm
Housing material	ABS
Installation location	Integration / surface mounting
Installation type	Surface mounting/recessed mounting
Length	48 mm
Max. operating temperature	50 °C
Min. operating temperature	-10 °C
PSTI conformity required	No
Sensor type	Reed contact
Type of detection	Magnetic field measurement
VdS class	none
Width	11 mm
EAN	4043158000191

Technical data - Proximity Chip Sticker, 5pcs. Set Smartvest/Terxon SX

Colour	White
Dimensions	(HxD) 0,5x25 mm
Height	0,5 mm
PSTI conformity required	No
Width	25 mm
EAN	4043158054033