

# Secvest Mini Wireless Magnetic Contact (white)

Art.-Nr. FUMK50020W

Seite 1 von 2



Unobtrusive and reliable securing of windows and doors

The Secvest mini wireless opening detector is especially compact and discreet. It consists of a detector and a magnet. These components are mounted parallel to each other on the moving part of the window or door and on the window or door frame. The detector triggers as soon as the distance between the two contact points is increased when the window or door is opened and informs the alarm panel. The Secvest mini wireless opening detector is available in white, brown and silver.

## Technologies

- Compact, discreet design
- Reliably detects opening of windows and doors
- Tamper monitoring

## Technical data - Secvest Mini Wireless Magnetic Contact (white)

Battery - max. battery life	3 y
Battery - quantity	1
Battery - type	3.6 V Lithium 1/2 AA
Certifications	compliant to EN 50131-1
Colour	white
Compatible with	Secvest, Terxon, BUM060040
DC voltage supply	3,6 V
Dimensions	(WxHxD) 28x42x18 mm
Environmental class	I
Gross weight	0,09 kg
Height	42 mm
Housing material	ABS

# Secvest Mini Wireless Magnetic Contact (white)

Art.-Nr. FUMK50020W

Seite 2 von 2

## Technical data - Secvest Mini Wireless Magnetic Contact (white)

Installation location	Windows, doors
Language of instructions	DE, UK, FR, NL, DK, IT
Length	18 mm
Max. operating temperature	55 °C
Max. transmission range (building)	30 m
Max. transmission range (free field)	100 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0,06 kg
PSTI conformity required	No
Radio frequency	868 MHz
Radio power	10 mW
Sabotage monitoring	Yes
Security level	2
Sensor type	Reed contact
Status display	Yes
Type of detection	Magnetic switch
VdS class	none
Voltage monitoring	Yes
Width	28 mm