

Secvest Wireless Remote Control

Art.-Nr. FUBE50012

Seite 1 von 2

Convenient operation of the alarm panel

The bidirectional wireless remote control is a practical accessory for operating the wireless alarm systems in the Secvest range at the push of a button. It also allows the current system configuration status to be viewed at any time.

Secure arming - long range

The remote control is used to easily arm and disarm the alarm system from a distance. Thanks to eight integrated LEDs, real-time feedback is provided regarding changes to the system status. The transmission range is approx. 30 metres.

Rapid assistance in an emergency

Simultaneously pressing the 'arm' and 'disarm' buttons triggers a panic alarm. This protects not only property but also the health and safety of residents.

Useful convenience functions

The fourth button can be freely programmed. In addition to internal arming, this can be used to switch an output (e.g. garage door control). This button is programmed directly at the alarm panel.

Secure radio communication

The remote control is protected with the Secvest alarm panel (Secvest and/or Secvest Touch) against so-called replay attacks by a secure radio procedure. This procedure for protection against manipulation by third parties exceeds the requirements of the security standard DIN EN 50131-1 Grade 2

Available in the variants: FUBE50015 (downward compatibility with Secvest 2WAY and Secvest IP) and FUBE50014 (only compatible with FUAA50xxx).

Technologies

- User-friendly remote control with easily recognisable key icons
 - For operation with the Secvest, Secvest IP and Secvest 2WAY wireless alarm systems
 - 8 LEDs for a clear display and current status feedback
 - Button for custom configuration available (Secvest wireless alarm system only)
 - Optional manual panic alarm available (Secvest wireless alarm system only)
 - Communicates with the Secvest and Secvest Touch via a secure wireless connection
-

Secvest Wireless Remote Control

Art.-Nr. FUBE50012

Seite 2 von 2

Technical data - Secvest Wireless Remote Control

Battery - max. battery life	2 years(s)
Battery type	CR2450 3V Li-Mn (FU2987)
Certifications	VdS (H 114001)
DC power supply	3 V
Display type	LED
Environmental class	II
Height	17 mm
Housing material	ABS
Language Manual	DE, UK, FR, NL, DK, PL
Language Packaging	DE, UK, FR, NL, DK, PL, ES, SE, IT
Length	62 mm
Max. Air humidity	75 %
Max. Operating temperature	40 °C
Max. Receive range (building)	30 m
Max. Receive range (free field)	200 m
Max. Transmit range (free field)	200 m
Max. Transmitting range (building)	30 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0.026 kg
PSTI conformity needed	No
Product group	Operation
Radio frequency	868 MHz
Radio power	10 mW
Security gradient	2
Technology	Electronics
Voltage monitoring	Yes
WEEE group	09
width	36 mm