

Secvest Wireless Info Module

Art.-Nr. FUM050030

Seite 1 von 2



Acoustic and visual indication of system status

The Secvest wireless info module is an optional Secvest accessory. An LED display and various signal tones are used to indicate all processes and alarm system statuses. For example, input and output delays are indicated by a feedback tone via the info module. Faults, information on sub-areas, and zone statuses are also displayed on the info module. If an alarm is triggered, the internal piezo sounder also generates an internal alarm of about 90 dB.

Technologies

- Provides Secvest status information
- 8 LED displays
- Various signal and alarm tones
- Integrated piezo sounder

Technical data - Secvest Wireless Info Module

Battery - type	none
Compatible with	Secvest, Terxon
Connections	12V
DC voltage supply	9-14 V
Depth	40,7 mm
Dimensions	(WxHxD) 124x124x40.7 mm
Display	8 LEDs of different colors
Environmental class	II
Height	124 mm
Housing material	ABS
IP protection class	54
Installation location	Indoors

Secvest Wireless Info Module

Art.-Nr. FUM050030

Seite 2 von 2

Technical data - Secvest Wireless Info Module

Installation type	Surface mounted
Integrated siren	Yes
Length	40,7 mm
Max. humidity	96 %
Max. operating temperature	55 °C
Max. receiving range (building)	30 m
Max. receiving range (free field)	100 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0,2 kg
PSTI conformity required	No
Power consumption	53 mA
Radio frequency	868,6625 MHz
Sabotage monitoring	No
Security level	2
Sound pressure	90 dB
Width	124 mm