

Secvest Wireless Key Switch

Art.-Nr. FUBE50060

Seite 1 von 2



Never forget your code again

The Secvest wireless key switch is an optional accessory for the Secvest wireless alarm system. It makes convenient arming and disarming of the alarm system possible with just the turn of a key. It is no longer necessary to enter a code on the central alarm panel and the alarm system can be armed and disarmed on the central alarm panel or the control panel by turning the key.

Clear status display - reliable transmission

Two integrated LEDs indicate the system status. The risk of a false alarm caused by an operative fault is therefore mitigated. The alarm panel and its components communicate over a secure wireless frequency exclusively reserved for the security industry. Protection class IP55 allows use of the wireless key switch in protected outdoor areas.

Technologies

- Convenient arming and disarming of the alarm panel by turning a key
- Sturdy housing
- Cylinder guard

Technical data - Secvest Wireless Key Switch

Battery - max. battery life	2 y
Battery - type	3.6 V AA Li battery (FU2992) or 12 V DC
DC voltage supply	3,6/12 V
Dimensions	(WxHxD) 87x117x47 mm
Environmental class	II
Height	117 mm
Housing material	Aluminium and plastic
IP protection class	55

Secvest Wireless Key Switch

Art.-Nr. FUBE50060

Seite 2 von 2

Technical data - Secvest Wireless Key Switch

Installation location	Indoors and protected outdoor areas
Length	47 mm
Max. operating temperature	55 °C
Max. receiving range (building)	30 m
Max. receiving range (free field)	100 m
Max. transmission range (building)	30 m
Max. transmission range (free field)	100 m
Min. operating temperature	-10 °C
Net weight	0,55 kg
PSTI conformity required	No
Power consumption	36 mA
Radio frequency	868,6625 MHz
Radio power	10 mW
Sabotage monitoring	Yes
Status display	Yes
Voltage monitoring	Yes
Width	87 mm