Smartvest Wireless Siren



Art.-Nr. FUSG35000A Seite 1 von 2



To be able to provide alarming both indoors and outdoors, the Smartvest Wireless Siren is fitted with a loud siren (up to 100dB) and a red LED strobe light. Battery operation (battery life: up to two years) means no wiring is required during installation; when the battery is low, the alarm panel is notified immediately. To be able to guarantee real security, the Smartvest Wireless Siren is fitted with tamper protection in the form of an anti-removal wall contact.

Technologies

- Smartvest extension for sounding alarms indoors and outdoors
- Quick and cable-free installation without the need for wires thanks to battery operation
- High-volume siren (up to 100 dB) and red LED strobe light for alarms with deterrent effect
- Sturdy, weatherproof siren (IP44)
- Automatic supervision, with functional tests repeated daily and feedback sent to the Smartvest alarm control panel
- Low battery notification sent to the Smartvest alarm control panel
- Battery life of up to 2 years
- Tamper protection provided by anti-removal wall contact

Technical data - Smartvest Wireless Siren

| Alarming | Acoustic warning signal |
|-----------------------------|-------------------------|
| Area of application | Outside / Inside |
| Battery - battery operation | Yes |
| Battery - max. battery life | 1 y |
| Battery - quantity | 4 |
| Battery - type | C (1,5V) |
| Colour | White |
| Compatible with Secvest | No |
| Compatible with Smartvest | Yes |





Art.-Nr. FUSG35000A Seite 2 von 2

Technical data - Smartvest Wireless Siren

| DC voltage supply | 5 V |
|----------------------------|--|
| Dimensions | (B x L x H) 112 x 122 x 300 mm |
| Gross weight | 0,19 kg |
| Housing material | Plastic |
| IP protection class | 44 |
| Light source | LED |
| Luminous colour | Red |
| Max. humidity | 80 % |
| Max. operating temperature | 50 °C |
| Min. humidity | 10 |
| Min. operating temperature | -10 °C |
| Net weight | 0,82 kg |
| Plug type | DC-plug: 3,5 x 1,35mm |
| Power consumption | 200 mA |
| Radio frequency | 868 MHz |
| Radio modulation | FSK |
| Sound pressure | 100 dB |
| Standby power consumption | 0,2 mA |
| Tamper protection | Yes |
| Transmission power | 4,5 dBm |
| Wireless range | (Depending on installation) 30 - 100 m |