

# Secvest Wireless Outdoor Sounder

Art.-Nr. FUSG50100

Seite 1 von 2

## Reliable alerting

The wireless outdoor sounder with LED flashing bar is the crucial component of a completely wireless alarm chain. If an alarm is triggered, the sounder generates a very loud signal tone with 100 dB of sound pressure. The red LED light flashes too (flashing frequency 1 Hz). The flashing light and sounder can be configured separately. This allows the flashing light to continue flashing while the signal tone stops after a set time.

## Protection against tampering

The sounder communicates with the Secvest alarm panel via the 868 MHz frequency, which is specially reserved for the security sector. The cover and seal contact provide the wireless outdoor sounder with targeted protection against tampering. The optimised seal contact has a precision adjustment option so can be adapted for any wall surface. If someone tampers with the device, the wireless outdoor sounder automatically sounds the alarm or forwards the tamper message to the Secvest alarm panel.

## Easy installation

The new, attractive design not only makes the wireless outdoor sounder an eye-catcher, but also makes it easier to install. As the cover on the front flap is fixed in place with a hinge, it is also possible to install the sounder with one hand.

## Technologies

- New, attractive design
- Loud combination sounder
- LED light displays different functions (e.g. confirmation of activation)
- Robust, UV-resistant, weatherproof housing
- Bright SMD LEDs

## Technical data - Secvest Wireless Outdoor Sounder

Battery - max. battery life	2 years(s)
Certifications	INCERT, VSÖ, EN
Current consumption	225 mA
Dimensions	(WxHxD) 210,6 x 294 x 78,5 mm
Height	294 mm
Illuminant	LED
Language Manual	DE, EN, DA, NL, FR, ES
Language Packaging	DE, EN, DA, NL, FR, ES, SE, IT, PL
Length	78.5 mm
Light color	Red
Max. Air humidity	93 %

# Secvest Wireless Outdoor Sounder

Art.-Nr. FUSG50100

Seite 2 von 2

## Technical data - Secvest Wireless Outdoor Sounder

Max. Operating temperature	60 °C
Max. Receive range (building)	30 m
Max. Receive range (free field)	100 m
Max. Transmit range (free field)	100 m
Max. Transmitting range (building)	30 m
Min. operating temperature	-25 °C
Modulation	FM
Mounting location	Outdoors
Net weight	1.781 kg
PSTI conformity needed	No
Power	1.5 W
Product group	Sirens and sounders
Protection class IP	65
Radio power	10 mW
Sound pressure	100 dB
Tamper monitoring	Yes
Voltage monitoring	Yes
WEEE group	09
width	210.6 mm