

# Signal Amplification Kit

Art.-Nr. TVAC17520

Seite 1 von 2



This complete kit including 5 dB antenna, wall mount and 2 m cable is ideal for improving signal strength and extending the range of wireless and Wi-Fi cameras. The sturdy wall mount, weather-protected cable and weather-protected antenna enable smooth installation. The antenna is compatible with all RP-SMA connections with a fine thread (45 threads per inch).

Suitable for TVAC14010, TVAC15010, TVAC1601x, TVAC18010, TVAC19x00, PPIC3xxxx, PPDF1xxxx.

## Technologies

- Complete kit including 5 dB antenna, wall mount and 2 m cable
- Ideal for improving signal strength and extending the range of wireless and Wi-Fi cameras
- Sturdy wall mount and weather protected cable and antenna
- Suitable for TVAC14010, TVAC15010, TVAC1601x, TVAC18010, TVAC19x00, PPIC3xxxx, PPDF1xxxx

## Technical data - Signal Amplification Kit

Cable diameter	6 mm
Cable length	2 m
Connections	SMA plug
Dimensions	(ØxH) 30x320 mm
Gain	5 dB
Height	320 mm
Impedance	50 Ω
Intended use	Indoors and outdoors
Max. operating temperature	60 °C
Min. operating temperature	-30 °C
Net weight	0,29 kg
Opening angle hori.	360 °
Power consumption	10 W

# Signal Amplification Kit



Art.-Nr. TVAC17520

Seite 2 von 2

---

## Technical data - Signal Amplification Kit

Width	30 mm
-------	-------