

CodeLoxx Remote Proximity Protokoll Security

Art.-Nr. CLX-LPXA-RP-10

Seite 1 von 2



Technical data - CodeLoxx Remote Proximity Protokoll Security

| | |
|-------------------------------------|---|
| Annual profiles | 6 |
| Area of application | Doors with PZ mortise lock, multiple locking, panic lock (approved for locking nose with free-wheel function) |
| Colour | Stainless steel |
| Combination code | No |
| DC voltage supply | 3 V |
| Drill protection | Security |
| Electronics | Remote with logging function |
| Emergency power supply possible | Yes |
| Event memory | 1000 |
| Inner knob diameter | 33 mm |
| Inner knob length | 49 mm |
| Locking media | ABUS Seccor chip key EM4102, Hitag 1 and Hitag 2 transponder |
| Logging and time function | Yes |
| Material | Stainless steel knobs, plastic cap inside |
| Max. number of locking media | 511 |
| Max. operating temperature indoors | 60 °C |
| Max. operating temperature outdoors | 60 °C |
| Min. operating temperature indoors | -10 °C |
| Min. operating temperature outdoors | -20 °C |
| Modularly extendible | Yes |
| Opening time can be set | between 6 and 12 seconds |
| Outer knob diameter | 30 mm |
| Outer knob length | 39 mm |
| Permanent access | Yes |
| Programming | Via programming key and/or PELT or SKM with TG-SKM |

CodeLoxx Remote Proximity Protokoll Security

Art.-Nr. CLX-LPXA-RP-10

Seite 2 von 2

Technical data - CodeLoxx Remote Proximity Protokoll Security

| | |
|-----------------------------|--------------------------------------|
| Protection class IP Indoor | 55 |
| Protection class IP Outdoor | 55 |
| Reader type | Chip key reader and proximity reader |
| Signalling | optical |
| Special design axle | For doors with PZ perforation |
| Standard length | Length measurement when ordering |
| Weekly profiles | 30 |
| ZAAP | No |