

# CodeLoxx Remote Proximity Protokoll Panik Security

Art.-Nr. CLX-LPXA-RP-10-P

Seite 1 von 2

## Technical data - CodeLoxx Remote Proximity Protokoll Panik Security

Annual profiles	6
Areas of application	Panic locks compliant with DIN179, which require a defined locking nose position, doors with PZ mortise lock
Closing media	ABUS Seccor chip key EM4102, Hitag 1 and Hitag 2 transponder
Colour	Stainless steel
Combination code	No
DC power supply	3 V
Degree of protection IP Interior	55
Degree of protection IP Outdoor	55
Diameter inner knob	33 mm
Drill protection	Security
Electronics	Remote with logging function
Emergency power supply possible	Yes
Event memory	Yes
Length inner knob	59 mm
Length outer knob	39 mm
Material	Stainless steel knobs, plastic cap inside
Max. Air humidity	80 %
Max. Max. number of locking media	511
Max. Operating temperature inside	60 °C
Max. Operating temperature outside	60 °C
Min. operating temperature inside	-10 °C
Min. operating temperature outside	-20 °C
Modularly extendable	Yes
Net weight	0.513 kg
Number of cycles/battery	50,000
Opening time adjustable	between 6 and 12 seconds
Outer knob diameter	30 mm

# CodeLoxx Remote Proximity Protokoll Panik Security

Art.-Nr. CLX-LPXA-RP-10-P

Seite 2 von 2

## Technical data - CodeLoxx Remote Proximity Protokoll Panik Security

Permanent access	Yes
Product group	Access control
Programming 1	Via programming key and/or PELT or SKM with TG-SKM
Protocol and time function	Yes
Reader type	Chip key reader and proximity reader
Special version Axis	For doors with PZ perforation
Standard length	Length measurement when ordering
WEEE group	09
Weekly profiles	30
ZAAP	Yes
signaling	optical