

ABUS Smart Security World Wi-Fi Tube Camera

Art.-Nr. PPIC34520

Seite 1 von 3

The ABUS Smart Security World Wi-Fi Outdoor Camera with Full HD 1080p resolution and infrared night vision function always ensures a brilliant image quality and a full overview. The camera is suitable for outdoor use and belongs to the IP66 protection class.

Event notification and mobile access

Operation and access to this app camera are exclusively via the app - with no PC, web browser or additional software. Movements in the camera's field of vision trigger recording to the SD card. If desired, you will be informed of incidents by email or push notification and can take a snapshot or access the corresponding video image data using the app. With the app, you always have access to the image material. The compressed data transmission means hardly any burden is placed on the network.

Smart Security World Ready

The ABUS Smart Security World Wi-Fi Outdoor Camera is part of the Smart Security World and is therefore not only functional, but is also fully integrated into the Smartvest wireless alarm system - as such, during installation there are no concessions in terms of convenience, and users simply follow the intuitive step-by-step installation instructions.

Information on the night vision function

The effective IR range will depend on the installation location.

Technologies

- For flexible outdoor use
- User friendly, intuitive setup of remote access to the camera
- Full HD 1080p resolution and infrared night vision function for brilliant image quality
- Recording to SD card with up to 128 GB (accessory)
- Direct notification via email and push service as well as automatic recording when motion detection is set up
- Professional motion detection for outdoor use (integrated PIR sensor)
- Guided step-by-step installation via app (iOS, Android)
- Integrated microphone for listening via the app (can be turned off)
- Low network load thanks to high data compression (H.264 High Profile compression)

Technical data - ABUS Smart Security World Wi-Fi Tube Camera

Alarm generation	Push notification / E-Mail
Article program	Comfort
Audio bit rate	16 Kbit/s
Base event	PIR / Software + Motion Mask
Channel width	20 MHz
Colour	Silver

ABUS Smart Security World Wi-Fi Tube Camera

Art.-Nr. PPIC34520

Seite 2 von 3

Technical data - ABUS Smart Security World Wi-Fi Tube Camera

Compatibility	Smartvest wireless system
Compatible with	Smartvest / SmartFriendsBox
Compatible with Secvest	No
Compatible with Smartvest	Yes
Compatible with wAppLoxx	No
Controllable with app	Yes
DC power supply	5 V
Day/night switching	Auto
Dimensions	(B x L x H) 105 x 65 x 190 mm
Encryption	AES 128bit, WPA/WPA2-PSK
Focal length	4 mm
Frequency range	2,400 –2,485 GHz
Gross weight	0.85 kg
Horizontal viewing angle	90 °
Housing material	Aluminium
IR LEDs	Yes
IR range (up to)	12 m
IR swivel filter	Yes
Image sensor	1/2,7" CMOS
Location	Outdoor use
Loudspeaker	No
Max. Air humidity	90 %
Max. Operating temperature	50 °C
Max. Resolution @ frame rate	Full HD (1080p) @ 20fps
Microphone	Yes
Min. humidity	20
Min. operating temperature	-10 °C
Minimum illumination (IR)	0 lx
Minimum illumination (color)	1 lx
Net weight	0.37 kg
Network connection	Micro-USB (10/100 Mbit/s)
Network connection WLAN	IEEE 802.11 b/g/n
Network protocols	TCP/IP, UDP, SMTP, NTP, DHCP, ARP
Optical wavelength	850
PIR range	5 m
PIR viewing angle	90 °
PSTI conformity given	No
PSTI conformity needed	Yes
Plug type	DC-plug: 3,5 x 1,35mm

ABUS Smart Security World Wi-Fi Tube Camera

Art.-Nr. PPIC34520

Seite 3 von 3

Technical data - ABUS Smart Security World Wi-Fi Tube Camera

Power consumption	4 W
Power supply	Power adapter
Pre/post-alarm memory	2 Sec
Protection class IP	66
Radio functions	Night vision, Zoom
Radio range	(Depending on installation) 20 - 50 m
Recording modes	Manual / motion detection / PIR
Resolution modes	Full HD (1080p) / HD (720p) / VGA (480p)
Sensitivity	-90 dBm
Simultaneous network access	3
Software	App: ABUS App2Cam Plus (Android/iOS)
Storage	Micro-SD
Storage medium	Micro-SD (128GB)
Transmission power	11b: 17 +/- 1,5dBm / 11g: 14 +/- 1,5dBm / 11n: 12,5 +/- 1,5dBm
Vertical angle of view	45 °
Video bitrate	0,256 - 1,5
Video compression	H.264
WEEE group	09
White balance	AWB