

IP Tube 4 MPx (2.8 - 12 mm)

Art.-Nr. IPCB64520

Seite 1 von 4



The IP Tube provides video streams in 4 MPx resolution with up to 30 fps. The dust- and water-resistant IP67 housing is well suited for outdoor use. Due to integrated IR LEDs with a range of up to 50m, the camera can be used day and night. Access to the camera is possible at any time via app.

Best overview

The motor zoom lens with a focal length of 2.8 - 12 mm provides a horizontal viewing angle of 32°-114 °. Focal length and focusing can be adjusted conveniently and precisely remote via the web interface.

Recording and compatibility

The recording can be done either on an ABUS recorder, 3rd party video management software or locally on a microSD card. Furthermore, the camera is compatible with the ABUS Secvest alarm center and the ABUS access control system wAppLoxx.

Comfortable installation

The IP tube is mounted on the ceiling or optionally on the wall. We recommend the ABUS installation box (TVAC31350), which allows a protected cabling to wall or ceilings. The free "ABUS IP Installer" software is available for simple setup in the network. The software finds the camera quickly and easily within the network and supports during the installation process.

Note: The camera does not come with a power supply, as it can be powered via PoE.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

IP Tube 4 MPx (2.8 - 12 mm)

Art.-Nr. IPCB64520

Seite 2 von 4

Technologies

- 4 MPx Resolution: 2.688 x 1.520 @ 30 fps
- 2.8 - 12 mm motor zoom lens
- Ultra low-light performance for excellent results in low-light environments
- 120 dB WDR function to compensate for image contrasts
- Vandalism and weather protected housing (IK10 & IP67)
- IR LEDs (range up to 50m)
- Supports H.264, H.265, MJPEG (incl. dynamic GOP)
- microSD card slot for internal data storage
- 12 V DC & PoE (802.3at)

Technical data - IP Tube 4 MPx (2.8 - 12 mm)

| | |
|---|--|
| Alarm input (NO/NC) | 1 |
| Alarm output | 1 |
| Alarming | E-Mail, NAS, FTP |
| Aperture at minimum illumination (colour) | F1.4 |
| Audio | 2-Way Audio (Browser, CMS) |
| Backlight compensation | WDR, BLC, HLC |
| Camera type | Tube |
| Colour | RAL9003 |
| Compatible with | NVR, Hybrid DVR, IPCam Plus |
| Compatible with ABUS Link Station | Yes |
| Compatible with Secvest | Yes |
| Compatible with wAppLoxx | Yes |
| Compatible with wAppLoxx Pro | Yes |
| Connections | 1 x RJ45, 1 x DC, 1 x video output, 1 x audio output, 1 x audio input, 1 x alarm input, 1 x alarm output |
| DC voltage supply | 12 (+/-10 %) V |
| Day/night switching | ICR/Color/B/W |
| Design | Tube |
| Dimensions | (LxWxH) 390x160x160 mm |
| Dynamic range (WDR) | 120 dB |
| Electronic shutter | 1/3 - 1/1000000 s |
| Encryption | HTTPS |
| Focal length | 2,8 – 12,0 mm |
| Frame rate | 1/16, 1/8, 1/4, 1/2, 1, 2, 4, 6, 8, 10, 12, 15, 16, 18, 20, 22, 25, 30 fps |

IP Tube 4 MPx (2.8 - 12 mm)

Art.-Nr. IPCB64520

Seite 3 von 4

Technical data - IP Tube 4 MPx (2.8 - 12 mm)

| | |
|-------------------------------|--|
| Functions | Scene Change Detection |
| Height | 160 mm |
| Horizontal viewing angle | 32 – 114 ° |
| ICR day/night function | Yes |
| IP protection class | 67 |
| IR LEDs | Yes |
| IR range (up to) | 50 m |
| Image enhancement | WDR, BLC, HLC, 3D DNR, Vertical Display |
| Image sensor | 1/2.5" Progressive Scan CMOS |
| LAN network access | RJ45 10M/100M self-adaptive |
| Language of instructions | DE, UK, FR, NL, DK |
| Length | 390 mm |
| Lens | Motor-Zoom |
| Max. humidity | 95 % |
| Max. operating temperature | 60 °C |
| Max. resolution @ frame rate | 2688 x 1520 @ 30 fps |
| Microphone | No |
| Min. operating temperature | -30 °C |
| Minimum illumination (IR) | 0 lx |
| Minimum illumination (colour) | 0,008 lx |
| Motion detection | 8 zones |
| Net weight | 1,2 kg |
| Network access | RJ45 |
| Network camera protocols | IPv4/v6, HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DynDNS, NTP, RTSP, TCP, UDP, DHCP, ONVIF Profile S, ONVIF Profile G, ABUS Server, Secvest Link |
| Noise reduction | 3D DNR |
| Number of IR LEDs | 4 |
| Number of streams | 3 |
| Number of users | 32 |
| ONVIF | Profile G, S, T |
| OSD language | DE, UK, FR, NL, DK |
| Optical zoom | 4.2 x |
| Other functions | Auto Backup Recording, Secvest Connectivity |
| Pixels (effective) | 2688(H) x 1520(V) pixel |
| PoE standard | IEEE 802.3at |
| Power consumption | 1.200 mA |
| Private zones | 4 |
| Protection class IK | 10 |

IP Tube 4 MPx (2.8 - 12 mm)

Art.-Nr. IPCB64520

Seite 4 von 4

Technical data - IP Tube 4 MPx (2.8 - 12 mm)

| | |
|------------------------------|---|
| Resolution | 4 MP |
| Resolution modes | Stream 1: 2.688 x 1.520 @ 25 fps, Stream 2: 640 x 480 @ 25 fps, Stream 3: 1.280 x 720 @ 25 fps |
| Simultaneous network access | 6 |
| Storage medium | microSD card, 256 GB (opt.) |
| Supported browsers | IE10, IE11, Mozilla Firefox 30.0+, Chrome 31.0+ |
| Technology | IP |
| Vertical viewing angle | 18 – 59 ° |
| Video Content Analysis (VCA) | Tripwire Detection, Intrusion Detection |
| Video compression | Stream 1: H.264, H.265, Dynamic GOP, Stream 2: H.264, H.265, MJPEG, Stream 3: H.264, H.265, MJPEG |
| Video network bandwidth | 32 kBit/s - 16 MBit/s |
| Video system | IP |
| White balance | AWB, Manual |
| Width | 160 mm |