

Analogue HD Tube 3 MPx (2.8 mm–12 mm)



Art.-Nr. HDCC63550

Seite 1 von 3

ABUS Analogue HD: Analogue images have never been so clear

The Analogue HD Tube 3 MPx has a high-quality image sensor for the surveillance of extensive indoor and outdoor areas. This ensures it provides a razor sharp and fluid image, for better detail recognition. The Analogue HD Tube 3 MPx with True WDR A high-performance True WDR function ensures evenly lit foregrounds and backgrounds in high-contrast light situations.

24/7 indoor and outdoor surveillance

The automatic day/night switching offered by the improved IR LED technology provides for better image lighting under varying light conditions. The Analogue HD Tube is robust in the face of wind and weather thanks to its IP67 protection class. Simple installation thanks to the motorised zoom lens and large range of ABUS brackets The installed camera is focussed easily via remote access using the recorder and can, therefore, be installed by just one person. The large range of brackets offers flexibility for any installation location.

Analogue HD technology: Ideal for inexpensive retrofitting

Using the infrastructure already installed offers flexible retrofitting possibilities. Simply exchange the cameras and recorders and get better performance from your existing video surveillance systems. You can continue to use your existing coaxial or 2-wire cable.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

Technologies

- 3 MPx Resolution: 1920 x 1536 @ 18 fps
- 42 % more image data compared to 2 MPx
- True WDR effectively compensates for light/dark contrast
- Easy installation and focussing via remote access with the motorised zoom lens (2.8–12 mm)
- Powerful IR LED technology for improved illumination of up to 40 m at night
- Weatherproof (IP67) for outdoor use
- Perfect for retrofitting: Transmission using conventional and existing CCTV infrastructure, such as coaxial or 2-wire cables
- Cable length of up to 500 m possible without loss
- Wide variety of holders for straightforward, cost-efficient installation
- Only compatible with Analogue HD Video Recorder HDCC90001, HDCC90011 and HDCC90021

Analogue HD Tube 3 MPx (2.8 mm–12 mm)

Art.-Nr. HDCC63550

Seite 2 von 3

Technical data - Analogue HD Tube 3 MPx (2.8 mm–12 mm)

AC power supply	24 V +/-15 % V
Amplifier control	AGC, 4 level
Aperture at minimum illumination (color)	1.2
Backlight compensation	True WDR
Camera outputs	1 x BNC (HD-TVI), 1 x BNC (FBAS)
Camera type	Tube
Colour	white
Compatible with Secvest	No
Compatible with wAppLoxx	No
Connections	1 x BNC (HD-TVI), 1 x BNC (FBAS), 1 x DC/AC (2-Pin)
Construction type of device	Tube
Current consumption	420 mA
DC power supply	12 V +/-15 % V
Day/night switching	Electromechanical IR cut filter
Dimensions	(LxWxH) 265x92x85 mm
Dynamic range (WDR)	120 dB
Electronic shutter	1/50 – 1/500000 s
Focal length	2.8 – 12 mm
Height	85 mm
Horizontal viewing angle	26.8 – 83.0 °
Housing material	Metal
IR LEDs	Yes
IR range (up to)	40 m
Image optimization	WDR, BLC, ATW, DNR
Image sensor	1/3" Progressive Scan CMOS
Length	265 mm
Lens	Motor-Zoom
Lens mount	14 mm
Max. Air humidity	90 %
Max. Operating temperature	60 °C
Max. Resolution @ frame rate	1920x1536 @ 18 frames/s (50Hz)/1920x1536 @ 18 frames/s (60Hz)
Microphone	No
Min. operating temperature	-40 °C
Minimum illumination (IR)	0 lx
Minimum illumination (color)	0.1 lx
Minimum lighting (B/W)	0.01 lx
Net weight	0.79 kg
Noise suppression	DNR

Analogue HD Tube 3 MPx (2.8 mm–12 mm)



Art.-Nr. HDCC63550

Seite 3 von 3

Technical data - Analogue HD Tube 3 MPx (2.8 mm–12 mm)

Optical zoom	4.2 x
PSTI conformity needed	No
Picture elements (total)	2052 x 1536
Power consumption	9 W
Protection class IP	67
Radio functions	Motion Detection, Tripwire Detection and Intrusion Detection via DVR
Resolution	3MPx
Resolution modes	1920 x 1536
Video channels HD-TVI	1
Video system	HD-TVI
WEEE group	09
White balance	ATW, manual
width	92 mm