

2-Wire Analog HD Transmission Set

Art.-Nr. TVAC25201

Seite 1 von 1

This 2-wire transmission set is used to establish alternative signal transmission instead of conventional coaxial cables, using (any existing) CAT5, CAT7 or 2-wire copper cables. Using the 2-wire set, you can transmit analogue video signals via a 2-wire cable. The set consists of a transmitter module and a receiver module. You can connect the transmitter module to the video output of your analogue HD camera, and you can connect the receiver module to the video input of your recorder. You can connect the two modules either with a twisted two-wire cable (CAT5 or CAT7 cable with RJ45 socket) or via existing 2-wire copper cables (e.g. a telephone cable). The maximum distance between the two modules is up to 300 metres, depending on the resolution of the transmitted data. The scope of delivery includes two adapters (2-pin connection), which you can use to easily implement the wiring.

Technologies

- Use of twisted pair or network cables for video transmission
- Set consisting of transmitter and receiver
- 1 x BNC plug (1 Vpp, 75 ohms)
- 1 x 2-pin connection
- Max. transmission distance: 300 m (2 MPx / 3 MPx), 150 m (5 MPx), 50 m (8 MPx)

Technical data - 2-Wire Analog HD Transmission Set

Dimensions	(W x H x D) 15 x 17 x 30 mm
Height	17 mm
Length	30 mm
Max. Operating temperature	55 °C
Min. operating temperature	0 °C
Net weight	0.04 kg
PSTI conformity needed	No
Product group	Accessories
Suitable cable	Twisted Pair/CAT5/CAT7
Transmission rate @ distance	300 m (2 MPx / 3 MPx), 150 m (5 MPx), 50 m (8 MPx)
Video input	1 x BNC
Video input impedance	75 Ω
Video input level	1 Vss dB
WEEE group	09
width	15 mm