

ABUS Z-Wave Security Set Protection against burglary

Art.-Nr. SHGW10410

Seite 1 von 5



The plus in safety

Protect yourself effectively against burglary with this set. If a break-in is detected via the opening detector or the multisensor, you will be alerted via the interior siren and via message on mobile terminals - this is called for more security in case of presence or absence. With the components included in the set, you form a basis for modern burglary protection, which you can expand step-by-step with further Z-Wave products from ABUS and other manufacturers.

Protection when you are at home

When you are at home, the opening detector protects windows and doors against unauthorised opening in case of breaking and entering. The sounder effectively scares off intruders and a push message to your smartphone informs you that there is a real threat.

Protection when you are away

When you are away, the motion detector ensures additional protection for your home. If windows or doors are opened or the motion detector is triggered, a local alarm method is activated. You can react appropriately even when away from the house, as the alarm will be transmitted to your mobile device by sending a push message to your smartphone.

Get more out of your Connected Home and expand this set with:

- hazard alarms such as the ABUS Z-Wave smoke or waterleak detector
- smart lighting with ABUS Z-Wave LED lamps
- a door lock drive for your front door with the ABUS HomeTec Pro Z-Wave
- a heating control with Z-Wave thermostats
- the roller shutter control with Z-Wave switching modules

In total, you can add up to 120 Z-Wave wireless components to the system and create up to 60 scenes (If - Then - When).

Technologies

ABUS Z-Wave Security Set Protection against burglary

Art.-Nr. SHGW10410

Seite 2 von 5

- Compact smart home control unit in Family Home Design with Z-Wave radio standard
- compatible to the ABUS Smartvest Wireless Alarm System
- extensive configuration options for up to 60 Scenes (if - then - when)
- Detects when windows and doors are opened and notifies your Smart Home gateway
- Simple and quick installation thanks to battery operation and adhesive installation
- High-volume siren (95 dB) and LED strobe light for alarms with deterrent effect
- 4 sensors in one device: motion sensor, thermometer, hygrometer and light sensor
- Detects movements by infrared within a radius of 110° and at a distance of 5 m
- extendable to a maximum of 120 Z-Wave radio components
- Mobile access from any location via the free app ABUS Z-Wave ONE (for iOS and Android)

Technical data - ABUS Z-Wave Security Set Protection against burglary

| | |
|--------------------------|-----|
| PSTI conformity given | No |
| PSTI conformity required | Yes |

Technical data - ABUS Z-Wave Gateway

| | |
|----------------------------|---|
| Alarming | Push notification / Acoustic warning signal |
| Backup power supply | No |
| Colour | White |
| Compatible with | Z-Wave devices (EU frequency: 868.42MHz) |
| Compatible with Secvest | No |
| Compatible with Smartvest | Yes |
| DC voltage supply | 5 V |
| Dimensions | (B x L x H) 96 x 21 x 96 mm |
| Display | LED |
| Encryption | AES128, SFTP, HTTPS |
| Gross weight | 0,38 kg |
| Housing material | Plastic |
| Loudspeaker | Yes |
| Luminous colour | Blue / Yellow / Red |
| Max. humidity | 80 % |
| Max. operating temperature | 50 °C |
| Min. humidity | 20 % |
| Min. operating temperature | 0 °C |
| Net weight | 0,233 kg |
| Network access | RJ-45 connector (10/100 Mbps) |
| Number of components | 120 |
| Number of events | 1.000 |
| Number of rooms / groups | 40 |
| Number of scenes | 60 |

ABUS Z-Wave Security Set Protection against burglary

Art.-Nr. SHGW10410

Seite 3 von 5

Technical data - ABUS Z-Wave Gateway

| | |
|-----------------------------|--|
| Number of users | 15 |
| Radio frequency | 868,42 MHz |
| Radio modulation | Z-Wave Plus (S2) / FSK (BFSK / GFSK) |
| Simultaneous network access | 10 |
| Software | App: ABUS Z-Wave One (Android / iOS) |
| Transmission power | 4,5 dBm |
| User levels | 3 |
| Wireless range | (Depending on installation) 20 - 100 m |
| EAN | 4003318841453 |

Technical data - ABUS Z-Wave Magnetic Contact

| | |
|-----------------------------|---|
| Area of application | Inside |
| Battery - battery operation | Yes |
| Battery - max. battery life | 3 y |
| Battery - quantity | 1 |
| Battery - type | CR2 (3V) |
| Colour | White |
| Compatible with Secvest | No |
| Compatible with Smartvest | No |
| Dimensions | (B x L x H) Sensor: 26 x 21 x 72 mm / Magnet: 11 x 15 x 35 mm |
| Display | LED |
| Gross weight | 0,125 kg |
| Housing material | Plastic |
| Max. humidity | 95 % |
| Max. operating temperature | 40 °C |
| Min. humidity | 10 % |
| Min. operating temperature | 0 °C |
| Net weight | 0,045 kg |
| PSTI conformity given | No |
| PSTI conformity required | Yes |
| Power consumption | 30 mA |
| Radio frequency | 868,42 MHz |
| Radio modulation | Z-Wave Plus (S2) / FSK (BFSK / GFSK) |
| Sensor type | Reed contact |
| Standby power consumption | 0,006 mA |
| Tamper protection | Yes |
| Transmission power | 4,5 dBm |
| Type of detection | Solenoid switch |
| Wireless range | (Depending on installation) 20 - 100 m |
| EAN | 4003318841491 |

ABUS Z-Wave Security Set Protection against burglary

Art.-Nr. SHGW10410

Seite 4 von 5

Technical data - ABUS Z-Wave Multisensor

| | |
|----------------------------------|--------------------------------------|
| Air humidity measuring accuracy | 5 % |
| Air humidity measuring range | 0 - 100 % |
| Air humidity resolution | 1 % |
| Area of application | Inside |
| Battery - battery operation | Yes |
| Battery - max. battery life | 2 y |
| Battery - quantity | 1 |
| Battery - type | AA (1,5V) |
| Colour | White |
| Compatible with Secvest | No |
| Compatible with Smartvest | No |
| DC voltage supply | 5 V |
| Dimensions | (Ø x L) 51 x 68 mm |
| Display | LED |
| Gross weight | 0,15 kg |
| Housing material | Plastic |
| Light sensor measuring accuracy | 1 lx |
| Light sensor measuring range | 0 - 65528 lx |
| Max. humidity | 95 % |
| Max. operating temperature | 40 °C |
| Min. humidity | 10 % |
| Min. operating temperature | 0 °C |
| Net weight | 0,068 kg |
| PIR range | 5 m |
| PIR viewing angle | 110 ° |
| PSTI conformity given | No |
| PSTI conformity required | Yes |
| Pet-proof | No |
| Plug type | Micro-USB |
| Power consumption | 38 mA |
| Radio frequency | 868,42 MHz |
| Radio modulation | Z-Wave Plus (S2) / FSK (BFSK / GFSK) |
| Sensor type | PIR |
| Standby power consumption | 0,015 mA |
| Tamper protection | No |
| Temperature measurement accuracy | 1 °C |

ABUS Z-Wave Security Set Protection against burglary



Art.-Nr. SHGW10410

Seite 5 von 5

Technical data - ABUS Z-Wave Multisensor

| | |
|-----------------------------|--|
| Temperature measuring range | 0 - 50 °C |
| Temperature resolution | 0,1 °C |
| Transmission power | 4,5 dBm |
| Type of detection | PIR: Heat detection |
| Wireless range | (Depending on installation) 20 - 100 m |
| EAN | 4003318841446 |