

Ceiling Mount for IPCS84510

Art.-Nr. TVAC31285

Seite 1 von 2



CEILING MOUNT FOR PTZ MINI-DOME CAMERA (IPCS84511)

Get your cameras in perfect position!

The ceiling mount for the IP mini dome camera with pan/tilt function (art. no. IPCS84511) is a robust and durable solution for mounting the camera indoors and outdoors. The aluminium construction ensures high stability and integrates seamlessly into any environment with its discreet white colour scheme. CRLF

With the compact mounting plate (diameter 120mm), the mount is securely attached to the ceiling in a space-saving way. The height of the extendable mount can be adjusted from 0.65m to 1.20m. This adapts the position and distance of the camera from the ceiling to the individual mounting situation. The cable routing integrated in the mount enables clean and professional installation, including optimum protection of the connecting cable against moisture, damage or tampering.

The ceiling mount is an optional accessory for the IP mini dome cameras of the IPCS84510 and IPCS84511 model series (and identical models). With the universal 1/4" (1/4-inch) thread of the tripod screw, the mount is also compatible with a wide range of other cameras. The load capacity of up to 2 kg with an own weight of approx. 1 kg must be noted.

Technologies

- Compatible with IPCS84510, IPCS84511
- Internal cabling is possible
- Sturdy aluminium construction for indoors and outdoors
- Color: white

Ceiling Mount for IPCS84510



Security Tech Germany

Art.-Nr. TVAC31285

Seite 2 von 2

Technical data - Ceiling Mount for IPCS84510

| | |
|------------------------|---|
| Colour | RAL9003 |
| Connection type | 1/4" Thread |
| Field of application | Extendable 0,65 m - 1,2 m, Indoor / Outdoor |
| Gross weight | 1 kg |
| Height | 650 mm |
| Housing material | Metal |
| Internal cable routing | Yes |
| Length | 120 mm |
| Load capacity | 2 kg |
| Net weight | 0,875 kg |
| Width | 120 mm |