

SRG92 ZS for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Seite 1 von 2



SECURITY FOR NARROW FRAME DOORS

Secure your front door with this door fitting

Front doors are always the object of desire for burglars. Since these are often inadequately secured, criminals often have an easy time of it. Door cylinders often protrude somewhat and can therefore be easily removed by force. Protect yourself against this method of break-in with a reliable door fitting including pulling protection. This door hardware was specially developed for front doors with a narrow frame profile and a door thickness of 57 to 65 millimetres. It has an automatic lever handle reset mechanism in the inside shield and cams that are variably adjustable to most common hole patterns. This makes assembly child's play.

Technologies

- Integrated pulling protection with cylinder cover
- Distance of cams adjustable to most common drilling patterns
- Handle on inside automatically returns to initial position
- Fixing screws hidden by decorative aluminium plate
- Just one version is necessary to cover cylinder protrusions from 7.5 - 12 mm
- Spacing: 92 mm, square bolt: 8 mm
- Easy fitting
- Outside shield with steel plate

Operation and use

- For universal use on narrow frames

SRG92 ZS for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Seite 2 von 2

- Grip plate outside, handle inside
- Suitable for door thicknesses of 59 - 69 mm

Variants

- Finishes: F1 (alu anodized), white
- Alternatively available as a handle/handle set

Technical data - SRG92 ZS for tubular frame doors in F1: Aluminum (Handle plate/Door handle)

Beidseitig Drücker	No
Cylinder protrusion	7,5 - 12 mm
Distance measure	92 mm
Door fitting for fire doors	No
Door type	Doors with tubular frames
Interchangeable fitting	Yes
Security Level Home Security	5
Weight	970 g
colour	F1: Aluminum Nature
pulling protection	Yes
EAN	4003318479564

Technical drawing

