

KLT512 for flat entrance doors in F1: Aluminum (Door handle on both sides)

Seite 1 von 2



HIGH STABILITY

House front doors and flat doors become more secure with this door fitting.

Inadequately secured doors make your home an easy target for burglars. Common security vulnerability: Door cylinders that stick out too far and can be easily unscrewed. Secure your doors with a reliable door fitting. Make your butt and rebated doors more secure with this door hardware. It consists of several layers of steel and can withstand a tensile load of 2.5 tonnes. Extra long steel cams with hardened and tempered special M6 screws increase protection against impact. A steel insert in the outer handle reliably prevents tearing. A secure complete package with VdS and DIN certificate for house front doors (HLT) with a thickness of 52 to 72 millimetres and flat front doors (KLT) with a thickness of 37 to 47 millimetres.

Technologies

- Certified according to DIN EN 1906 SK 2 and DIN 18 257 ES, VdS approved
- Maximum resistance due to the layer construction: several bottom plates for maximum protection
- · High impact resistance: extra long steel cams, complete with tempered special M6 screws
- An additional steel inset provides extra strong leverage/tear-off resistance
- Grip plate adjustable to DIN left and right doors
- Spacing: 72 mm, square bolt: 8 mm

Operation and use

- For main entrance doors (HLT) and apartment doors (KLT)
- · Suitable for rebated and flush doors, left and right opening



KLT512 for flat entrance doors in F1: Aluminum (Door handle on both sides)

Seite 2 von 2

- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 47 mm
- Mounting material for deviating door thicknesses can be supplied

Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), F3 (anodized brass), F4 (anodized bronze)
- Alternatively available as a handle/handle set

Technical data - KLT512 for flat entrance doors in F1: Aluminum (Door handle on both sides)

Beidseitig Drücker	Yes
Cylinder protrusion	12 mm
Distance measure	72 mm
Door fitting for fire doors	No
Door type	Apartment door
Interchangeable fitting	No
Security Level Home Security	6
Weight	1284 g
colour	F1: Aluminum Nature
pulling protection	No
EAN	4003318247903

Technical drawing





