

KLN314 F2 two handles CL/DNFLI



Technologies

- Certified according to DIN EN 1906 SK 1 and DIN 18 257 ES 0
- Increased leverage resistance: Solid cams plus inner screws
- Proven layered construction: Hardened steel bottom plate, plus sturdy cover
- Thickness: 15 mm
- Spacing: 72 mm, Square spindle: 8 mm

Operation and use

- For apartment doors
- Grip plate outside, handle inside
- Suitable for door thicknesses of 37 - 47 mm
- Mounting material for deviating door thicknesses can be supplied

Variants

- Finishes: F1 (alu anodized), F2 (silver anodized), F3 (anodized brass), F4 (anodized bronze), F9 (stainless steel look), white
- Alternatively available as a handle/handle set

Technical data - KLN314 F2 two handles CL/DNFLI

Beidseitig Drücker	Yes
Cylinder protrusion	15 mm
Distance measure	72 mm
Door fitting for fire doors	No
Door type	Apartment door
Interchangeable fitting	No

KLN314 F2 two handles CL/DNFLI

Technical data - KLN314 F2 two handles CL/DNFLI

Security Level Home Security	5
Weight	937 g
colour	F2: Aluminum Nickel Silver
pulling protection	No
EAN	4003318091797

Technical drawing

