

# RR40 for tubular frame doors (DIN R/L 40 24)

Seite 1 von 2



## THE NARROW SOLUTION

Narrow doors need narrow locks. The mortice lock is the solution.

Not all doors are the same. There are many that are narrower than others. But you must also be able to lock such doors securely. The tubular frame lock can be used on doors with narrow profiles. An extra-strong mechanism and high-quality materials made of metal and special steel make the lock a trustworthy solution for the security of your door. It is particularly suitable for doors with glass inserts and other narrow frames. Extra corrosion protection is provided by complete galvanic zinc plating. The lock can be fitted in doors with a distance measurement of 92 millimetres.

## Technologies

- High capacity of resistance by use of high quality materials
- Extra solid mechanical construction
- Metal latch and bolt
- Both counter and latch spring made from special steel
- Extra corrosion protection by electrolytic galvanizing
- Lockable with a single turn of the key

## Operation and use

- For doors with tubular frames
- When closing the door only the latch is being operated
- By locking the door cylinder the bolt is activated

# RR40 for tubular frame doors (DIN R/L 40 24)

Seite 2 von 2

- Can be used right or left as latch can be turned
- Forend 24 x 240 mm (angular)

## Variants

- Finish: galvanic zinc plated
- Available in backset: 25/30/35/40 mm

## Technical data - RR40 for tubular frame doors (DIN R/L 40 24)

Backset	40 mm
Distance measure	92 mm
Door type	Doors with tubular frames
Forend shape	angular
Lock control	Door cylinder
Opening direction	left/right
Security Level Home Security	7
Weight	553 g
Width forend	24 mm
colour	zinc plated
EAN	4003318353772

## Technical drawing

