## 9603 V white



Seite 1 von 2



#### CLOSES FIRE DOORS INDEPENDENTLY

Door closer for house, flat and fire doors for quiet and safe closing.

Safety-relevant for fire doors: With this door closer you can close house, flat and fire doors safely and quietly. The latter, in particular, must always be self-closing. This door closer closes with a closing speed that is continuously adjustable by means of a valve. It is suitable for doors with a width of up to 1.40 metres and has a self-regulating hydraulic opening absorber. In combination with the additionally available DIN plate, this door opener is also suitable for fire doors.

### **Technologies**

- Tested according to DIN EN 1154, closing force EN 3 6
- Closing speed can be adjusted using the valve regulator
- 2 closing ranges: 180° 15°; 15° 0°
- End latch adjustable by arm
- Closing delay can be adjusted using the valve regulator
- Dimensions: 245 x 46 x 60 mm
- Back check can be adjusted using the valve regulator

#### Operation and use

- For main entrance doors and apartment doors
- Suitable for door widths up to 1400 mm
- Can be used DIN R / DIN L
- Suitable for fire exit doors in Germany, DIN EN1154A
- Quick and easy fitting

#### **Variants**

- Finishes: silver, white
- Fitting plate available optionally

# 9603 V white



Seite 2 von 2

## Technical data - 9603 V white

Door type	Entry door
Door width	max. 1400 mm
Weight	2667 g
colour	white
EAN	4003318300820

## Technical drawing

