

Flush-mounted wireless remote unit

Art.-Nr. 501637

Seite 1 von 2



The wireless remote unit FR enables a seamless coupling of an external enabling system (e.g. time recording, access control) with these ABUS Security-Center door opening systems together with CodeLoxx, ZL and SLT.

Technologies

- Wireless remote unit FR for connection to an external switch contact
- For control of electronic double knob cylinders (CodeLoxx Remote) using 3 m wireless transmission

Technical data - Flush-mounted wireless remote unit

Annual profiles	6
Area of application	Control of electrical switching functions
Colour	White
Connections	Power supply, digital interface
Diameter	84,5 mm
Event memory	1000
Height	7 mm
Housing	Flush socket
Housing material	Plastic
Language of instructions	EN
Language packing	EN
Material	Plastic cover
Max. humidity	80 %
Max. number of locking media	511
Max. operating temperature indoors	60 °C

Flush-mounted wireless remote unit

Art.-Nr. 501637

Seite 2 von 2

Technical data - Flush-mounted wireless remote unit

Max. operating temperature outdoors	60 °C
Min. operating temperature indoors	-10 °C
Min. operating temperature outdoors	-10 °C
Net weight	0,1361 kg
OSD language	English
Opening time can be set	variable between 1 or 6 seconds
Operating mode	Relay as normally closed contact
Other dimensions	Plastic cover Ø 84.5 mm, height 7 mm (for flush sockets Ø 55 mm)
Power supply	Power supply via external power source (not included in scope of delivery): 9–24 V DC
Programming	With entry unit via Prog ACS or SKM
Weekly profiles	30