

Wall-mounted AEBasic evaluation unit

Art.-Nr. 501638

Seite 1 von 2



The AEB evaluation units from ABUS Security-Center are the intelligent intermediaries between the door and alarm system and thus signify an increase in security and comfort during operation.

Technologies

- AEBasic evaluation unit for arming/disarming burglar alarm systems
- Blocking of locking systems (CLX-/ SLT-/ ZL- Alarm AEBasic) via 3 m wireless transmission
- Control of electrical switching functions: electrical door openers, motorized locks, lighting etc.
- Wall mounting

Technical data - Wall-mounted AEBasic evaluation unit

| | |
|------------------------------|---|
| Additional functions | Optional when arming/disarming: configuration with or without status notification from the burglar alarm system |
| Area of application | Control of electrical switching functions |
| Colour | White |
| Connections | Power supply, digital and analogue interface |
| Height | 86 mm |
| Housing | Surface mounted |
| Housing material | Plastic |
| Language of instructions | EN |
| Language packing | EN |
| Length | 30 mm |
| Material | Plastic casing |
| Max. humidity | 80 % |
| Max. number of locking media | 255 |

Wall-mounted AEBasic evaluation unit

Art.-Nr. 501638

Seite 2 von 2

Technical data - Wall-mounted AEBasic evaluation unit

| | |
|-------------------------------------|---|
| Max. operating temperature indoors | 60 °C |
| Max. operating temperature outdoors | 60 °C |
| Min. operating temperature indoors | -10 °C |
| Min. operating temperature outdoors | -10 °C |
| Net weight | 0,1563 kg |
| OSD language | English |
| Operating mode | Relay as normally closed or normally open contact |
| Power supply | Power supply via external power source (not included in scope of delivery): 9–24 V DC; Switching power of the changeover relay 24 V AC/DC, 0.3 A |
| Programming | Via Prog ACS or SKM |
| Width | 86 mm |