

AE255F evaluation unit with housing

Art.-Nr. 501642

Seite 1 von 2



Intelligent circuits for more security and comfort are realised with the AE255F evaluation unit. It is thus able to specify in a targeted way which people may arm, disarm or use both functions. Users who only have access in a disarmed state can also be created. It is also possible to apply special codes for silent alarms, internal arming or special keys for the guard users.

Technologies

- Programmable evaluation unit AE255F for storage and evaluation of arming/disarming authorisations
- Arming/disarming of burglar alarm systems regarded as "inevitability".
- Suitable for multi-door systems: Up to 4 wireless receivers or entry units can be connected to an evaluation unit

Technical data - AE255F evaluation unit with housing

Additional functions	Choice of authorisations: access only or including arming/disarming; special codes: silent alarm, internal arming/disarming; special key: guard user; jumper 'VdS'
Area of application	Control of electrical switching functions
Colour	White
Connections	Power supply, digital and analogue interface
Height	180 mm
Housing	Surface mounted
Housing material	Plastic
Language of instructions	EN
Language packing	EN
Length	42 mm
Logging and time function	No
Material	Plastic casing
Max. humidity	80 %

AE255F evaluation unit with housing

Art.-Nr. 501642

Seite 2 von 2

Technical data - AE255F evaluation unit with housing

Max. number of locking media	255
Max. operating temperature indoors	60 °C
Max. operating temperature outdoors	60 °C
Min. operating temperature indoors	-10 °C
Min. operating temperature outdoors	-10 °C
Net weight	0,4821 kg
OSD language	English
Operating mode	VdS classes can be selected via jumper
Power supply	For connection to the burglar alarm system: 12 V DC
Programming	Via Prog ACS or SKM
Width	131 mm