

Wireless Outdoor Camera

Art.-Nr. TVAC18010B

Seite 1 von 2



Sturdy wireless outdoor camera for 24 h safety

This wireless outdoor camera serves as an extension of the digital wireless monitoring set from ABUS. Thanks to the solid, weatherproof design, it is ideal for outdoor areas. The VGA resolution and the infrared night view function ensure optimal video image data quality at any time of day or night. Integrated motion detection with an alarm function reliably detects movement and sets off an alarm if there is danger of unauthorised access.

Intuitive installation with app or QR code

Installation is done step-by-step using the app or the QR code, making it easy even for technical laymen. The app also allows access to up to four cameras of this type, making practical mobile monitoring possible.

The effective IR range will depend on the installation location. If there are surfaces that absorb light or no objects that reflect IR light in the field of view, the IR range will be reduced and/or the video image will be too dark. Reflective objects in the immediate vicinity of the camera (e.g. roof gutter or wall) may also result in the reflection of IR light, which can disturb the image.

Technologies

- Wireless outdoor camera for digital wireless monitoring set
- Simple step-by-step installation with app and QR code (iOS, Android)
- App access of up to 4 cameras
- VGA resolution and infrared night vision function
- Sturdy, weatherproof outdoor cameras (IP66)
- Professional integrated motion detection (PIR sensor) with alarm function
- Integrated motion detection (PIR sensor)

Wireless Outdoor Camera

Art.-Nr. TVAC18010B

Seite 2 von 2

Technical data - Wireless Outdoor Camera

Channel width	1 MHz
DC voltage supply	5 V
Dimensions	150 x 74 x 68 mm
Dwell time on a single carrier according to the pseudo-random principle	< 0.4 s
Frequency	2,4 GHz
Height	68 mm
IP protection class	66
IR swivel filter	Yes
Image sensor	1/4" CMOS
Length	150 mm
Lens	3,6
Max. operating temperature	50 °C
Maximum EIRP (Equivalent Isotropically Radiated Power)	< 100 mW
Min. operating temperature	-20 °C
Modulation	FHSS
Net weight	0,39 kg
Number of IR LEDs	6
Number of channels (pseudo-random principle)	15
Power consumption	550 mA
Range of night vision function	8 m
Resolution	640 x 480 (VGA)
Sensitivity	-80
Transmission channels	15
Transmission power	15
Width	74 mm
Wireless range	100 m