

# ELT proximity entry unit

Art.-Nr. 501843

Seite 1 von 2



The EL entry unit from ABUS Security-Center signifies efficiency and performance. In spite of the compact construction and the discreet design, this wall reader opens up numerous possibilities in combination with the SG control units or the AE255F evaluation units. This enables the operation of electric circuits such as motorized locks, lifts or automatic doors to be controlled via the insertion of a valid ABUS Seccor chip key, with code keypad or verification with a valid proximity medium. The EL entry unit is also suitable for activation of electrical door openers.

## Technologies

- Entry unit with code keypad, chip key reader and proximity reader for wall installation
- For connection to control units (SG-Vario, SG-Basic) for control of electric door openers, motorized locks, lifts, cabinets etc.
- For connection to evaluation units AE255(F), for arming/disarming burglar alarm systems
- Acoustic signal

## Technical data - ELT proximity entry unit

|                             |  |
|-----------------------------|--|
| Colour                      | Stainless steel  |
| Dimensions                  | Outside: 175 x 58 x 30 mm mm                                 |
| Environmental conditions    | Temperature min./ max.: -20/ 60, max. humidity: 80%          |
| Height                      | 175 mm   |
| Item abbreviation           | ELT-LCPxA-0  |
| Length                      | 30 mm  |
| Locking media               | ACS, T-Prox/K-Prox   |
| Power supply                | Control unit (SGP-Vario, SG-Basic) or AE255F evaluation unit |
| Programming                 | Via programming key and/or PELT or SKM with TG-SKM           |
| Protection class IP Outdoor | 44   |
| Signalling                  | Acoustic   |

# ELT proximity entry unit

Art.-Nr. 501843

Seite 2 von 2

---

## Technical data - ELT proximity entry unit

|       |       |
|-------|-------|
| Width | 58 mm |
|-------|-------|