

ABUS Analogue HD Video Surveillance 6-Channel Hybrid Recorder

Art.-Nr. TVVR33601

Seite 1 von 3



The recorder is ideal for hybrid/simultaneous operation of analog HD and IP cameras. It compresses video data via H.265 Plus and supports multiple analog video formats. Access to live images and recording is available via free app, web or CMS software - designed and supported in Germany.

Use advantages: Combine Analog HD and IP easily

The 6-channel hybrid recorder records video streams from 4 analog HD cameras and 2 compatible IP cameras in parallel - with 25 frames per second and a resolution of up to 4MPx per analog HD and 6MPx per IP camera. It supports the popular analog video formats TVI, AHD, CVI and CVBS, making it perfect for upgrading existing analog systems.

Easy commissioning and precise configuration

In just a few steps, the recorder is completely ready for operation (recommended: 3.5" SATA hard disk up to 6 TB) and can be operated via monitor and mouse. Depending on requirements, it records manually as well as by motion detection, stored schedule or permanently - thanks to H.265 Plus for strong compression of the video data 6x longer compared to H.264. Several modes help in the efficient search and playback. Access is via local user interface, web interface, CMS software or app - even from a distance.

Access to live images and recordings via App: secure and easy

The recorder simply connects directly to the ABUS Link Station app on the smartphone or tablet via an encrypted end-to-end connection (E2E) - without any router settings. With the Lite version of the app, up to 60 minutes of data stream (live view/playback) per month via Internet or WLAN are completely free. Or with the ABUS Link Station Pro: Buy once and access unlimited data forever.

Technologies

- 6-channel hybrid recorder for managing up to 6 cameras
- Flexible integration: up to 4 analog HD cameras with 2 MPx and simultaneously 2 IP cameras with up to 6 MPx. Use completely with IP cameras if required
- Record 4 times longer with H.265 Plus (depending on camera model)
- Optimized for retrofitting: supports TVI, AHD, CVI and CVBS formats
- Store up to 6TB on 3.5" hard disk (not included)
- Recording via motion detection, following a time schedule or continuously
- User-friendly app, web & PC software for live viewing and playback of video data
- Easy mobile access with the ABUS Link Station App - no router settings required
- Quiet operation (no fan)

ABUS Analogue HD Video Surveillance 6-Channel Hybrid Recorder

Art.-Nr. TVVR33601

Seite 2 von 3

Technical data - ABUS Analogue HD Video Surveillance 6-Channel Hybrid Recorder

| | |
|---|--|
| Alarming | Acoustic warning signal, OSD signal, e-mail |
| Audio input | 1x RCA (2.0Vp-p, 1kΩ) |
| Audio output | 1x RCA (Linear, 1kΩ) |
| Compatible with Secvest | No |
| Compatible with Smartvest | No |
| Compatible with wAppLoxx | No |
| DC voltage supply | 12 V |
| Dimensions | (W x L x H) 315 x 240 x 48 mm |
| Gross weight | 2,881 kg |
| HD-TVI video channels | 4 |
| Housing | 1U Chassis |
| Housing material | Metal, Plastic |
| IP video channels | 6 |
| Max. humidity | 90 % |
| Max. operating temperature | 55 °C |
| Max. resolution @ frame rate | TVI: 4MPx, 3MPx, 2MPx @ 30fps / 1MPx @ 60 fps AHD: 4MPx, 2MPx, 1MPx @ 30fps CVI: 2MPx, 1MPx @ 30fps CVBS: Support |
| Min. humidity | 10 % |
| Min. operating temperature | -10 °C |
| Net weight | 2,082 kg |
| Network access | 1x RJ-45 10/100 Mbit/s self-adaptive Ethernet interface |
| Network protocols | TCP/IP, DHCP, DNS, DDNS, NTP, SADP, SMTP, NFS, UPnP™, HTTPS |
| OSD language | DE, UK, FR, NL, DK, IT, PL, ES, SE |
| PSTI conformity required | No |
| Performance decoding (local live view & playback) | 4x 2MPx |
| Power | 14 |
| Recording modes | Manual, time schedule, motion detection, alarm |
| Recording resolution @ frame rate per camera | 4MPx Stream: 4MPx @ 15fps, 2MPx / 1MPx / WD1 / 4CIF / VGA / CIF @ 30 fps 3MPx Stream: 3MPx / 1MPx / WD1 / 4CIF / VGA / CIF @ 15 fps 2MPx Stream: 2MPx / 1MPx @ 15fps, WD1 / 4CIF / VGA / CIF @ 30 fps 1MPx Stream: 1MPx / WD1 / 4CIF / VGA / CIF @ 30 fps |
| Resolution HDMI output | 1920 × 1080 / 60Hz, 1280 × 1024 / 60Hz, 1280 × 720 / 60Hz, 1024 × 768 / 60Hz |
| Resolution VGA output | 1920 × 1080 / 60Hz, 1280 × 1024 / 60Hz, 1280 × 720 / 60Hz, 1024 × 768 / 60Hz |
| Software | ABUS Link Station (iOS & Android) / IP Installer |
| Storage medium | 1x Sata interface (3,5" HDD, max. 6TB) / NAS |
| Supported IP cameras | TVIP1156x, TVIP21560, TVIP41500, TVIP4x56x, TVIP41660, TVIP615x0, TVIP6x56x, TVIP82900 |

ABUS Analogue HD Video Surveillance 6-Channel Hybrid Recorder

Art.-Nr. TVVR33601

Seite 3 von 3

Technical data - ABUS Analogue HD Video Surveillance 6-Channel Hybrid Recorder

| | |
|--|--|
| Supported browsers | IE11 (Plugin) |
| Synchronous playback | 4 |
| Total network throughput (input/output) | 72 Mbit/s |
| Total video channels | 6 |
| USB connection | 2x USB 2.0 |
| Video compression | H.264 / H.264 Plus / H.265 / H.265 Plus / H.265 Plus Pro |
| Video input | 4x BNC (1.0Vp-p, 75Ω) |