

# PR2800 white length 1

Seite 1 von 2



## THE FLAGSHIP

Comfortably attached, bombproof hold: This security door bar secures reliably.

Make your wooden, metal and plastic doors more secure with this security door bar. No matter whether you use it for your house or flat door. The bolt secures doors across their entire width. These can range from 73.5 to 120 centimetres. A highlight: Assembly is particularly easy as the width of the transom can be adjusted with a telescopic tube body. In addition, a non-return device is used. The operation can take place inside as well as outside. The scope of delivery includes a high-quality ABUS Pfaffenhain cylinder.

## Technologies

- Secures the door over the whole width
- Telescopic tubular body for adaptation to different door widths
- Bolt with rebound protection
- For door widths from 735 - 1 200 mm
- Incl. anti-pull protected escutcheon and ABUS Pfaffenhain cylinder (30/60)
- Comfortable and quiet operation owing to the special metal drive components
- The locking direction can be changed
- Comprehensive accessories can be used
- Hardened bolt bars

## Operation and use

- For house or apartment entrance doors
- Can be operated inside and outside with a key
- Can be used for doors DIN R or DIN L
- Keyed alike cylinders can be combined with ABUS padlocks
- VdS-approved in conjunction VdS Class A or higher approved door cylinders
- Can also be used for outward opening doors with PA1018 accessories

## Variants

- Colours: brown, white, stainless-steel look
- Also available without a cylinder
- Available in 2 lengths (L1 and L2)
- Lockout length L1: min.: 1018 mm, max.: 1142 mm
- Lockout length L2: min.: 1238 mm, max.: 1362 mm

# PR2800 white length 1



Seite 2 von 2

- 
- PWA2700 wall anchor for optimal wall embedding
- 

## Technical data - PR2800 white length 1

Door width	735-980 mm
Security Level Home Security	10
Weight	7448 g
colour	white
pulling protection	Yes
type of cylinder	Double cylinder
EAN	4003318016899