

Secvest Wireless Remote Control

Art.-Nr. FUBE50013

Seite 1 von 2



Convenient operation of the alarm control panel

The wireless remote control is a practical accessory for the Secvest wireless alarm system. Its use enables the system to be operated at the simple touch of a button. It also allows the current system status to be queried at any time.

Reliable arming at long range

The remote control facilitates arming and disarming of the alarm system - even at great distances. Thanks to 8 integrated LEDs, real-time feedback is provided regarding changes to the system status. The transmission range is approx. 30 metres.

Rapid assistance in an emergency

Simultaneously pressing the 'arm' and 'disarm' buttons triggers a panic alarm. This protects both people and valuables effectively.

Display of additional information

By pressing the third button, important information about the status of the alarm control panel can be queried (armed, disarmed, internal protection active, fault). Feedback is immediately displayed on the remote control.

Useful convenience functions

The fourth button allows custom configuration, it can be set to control a garage door, for example. This button can be programmed directly on the alarm control panel.

Technologies

- User-friendly remote control with easily identifiable symbols
- Features 'arm', 'disarm' and 'status query' keys
- 8 LEDs provide an overview and display current system status

Secvest Wireless Remote Control

Art.-Nr. FUBE50013

Seite 2 von 2

- Button for custom configuration available (Secvest wireless alarm system only)
- Optional manual panic alarm available (Secvest wireless alarm system only)

Technical data - Secvest Wireless Remote Control

Battery - max. battery life	2 y
Battery - type	CR2450 3V Li-Mn (FU2987)
Certifications	VdS home, REQ
DC voltage supply	3 V
Dimensions	(WxHxD) 36,2 x 17 x 62 mm
Display	LED
Environmental class	II
Height	17 mm
Housing material	ABS
Language of instructions	DE, UK, FR, NL, DK, PL
Language packing	DE, UK, FR, NL, DK, PL, ES, SE, IT
Length	62 mm
Max. humidity	75 %
Max. operating temperature	40 °C
Max. receiving range (building)	30 m
Max. receiving range (free field)	200 m
Max. transmission range (building)	30 m
Max. transmission range (free field)	200 m
Min. operating temperature	-10 °C
Modulation	FM
Net weight	0,035 kg
PSTI conformity required	No
Radio frequency	868,6625 MHz
Radio power	10 mW
Security level	2
VdS approval no.	H 114001
VdS class	home
Voltage monitoring	Yes
Width	36 mm